

MARINE GENERATOR

750KVA CUMMINS Generator Set(Slient tyepe)

ISO9001 Supplier

Class Certificate

Export Supply

750KVA CUMMINS Generator set(Slient type) General feature Coupled with CUMMINS diesel engine and SUNAMA POWER alternator • 24V DC start motor and storage battery • Brushless, Self-excited, AVR, insulation c...



Key Highlights

Category	Marine Generator
Standard	DIN
Certificate	DNV,ABS,RINA,CCS,

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Generator	Model / SKU	750KVA-CUMMINS-Generator-Set-Slient-tyepe
Standard	DIN	Certificate	DNV,ABS,RINA,CCS,
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- 750KVA CUMMINS Generator set(Slient type)
- ENGINE SPECIFICATION
- General feature
- Alternator SPECIFICATION

750KVA CUMMINS Generator set(Slient type)

General feature

Coupled with CUMMINS diesel engine and SUNAMA POWER alternator

- 24V DC start motor and storage battery
- Brushless, Self-excited, AVR, insulation class H alternator

- 40°C radiator as standard, 50°C is optional
- Key start panel control system as standard, digital auto-start panel is optional
- Optional open type or silent type
- All generator sets are gone through rigorous testing before being released to the market place, including CUMMINS Diesel Engine

ENGINE SPECIFICATION

Engine Model KTAA19-G6A

Configuration: 4 cycle , 6cylinders in "L"

Aspiration: Turbocharged after water-cooled

Bore x Stroke: 159 x14259mm

Rated speed: 1800rpm

Displacement (Liter): 18.9L

Compression Ratio: 17.5 : 1

Output Power: 664KW/830KVA

Speed Governor: electrical

Cooling System: Water-cooled , 40°C Radiator As Standard, 50°C Is Optional.

Speed Stability (%): ≤5%

Fuel Consumption at 100% Load: 205g/kw.h

Starter Motor: DC24V

Alternator SPECIFICATION

Brand: SUNAMA POWER

Alternator Model: SMI-600-4

Capacity: 750KVA

Voltage: 120V/230V

Frequency & Speed: 60HZ/1800RPM

Exciter type: Brushless, Self-excited, AVR

Power factor :0.8

Voltage Adjust range: ≥5%

Voltage Regulation NL-FL: ≤±0.5%

Insulation Grade: H

Protection Grade:IP23