

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

HIGH HOLDING POWER ANCHOR

AC-14 HHP Anchor

AC-14 Type High Holding Power Anchor AC 14 Anchor is high holding power anchor, which was developed from stockless anchor; AC-14 HHP Anchor apply to all kinds of seabed(Mud, Soil, Sand, Sandstone, etc.), dig into...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	High Holding Power Anchor
Standard	DIN
Material	Casting Steel
Weight / Size	75KGS to 30000KGS
Certificate	ABS, LR, BV, DNV, GL, RINA, NK, KR, RS, IRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	High Holding Power Anchor	Model / SKU	AC-14-HHP-Anchor
Standard	DIN	Material	Casting Steel
Weight / Size	75KGS to 30000KGS	Surface	75KGS to 30000KGS Finish:
Certificate	ABS, LR, BV, DNV, GL, RINA, NK, KR, RS, IRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- AC-14 Type High Holding Power Anchor
- AC-14 Anchors Specification:
- AC-14 Anchor Weights:

AC-14 Type High Holding Power Anchor

AC 14 Anchor is high holding power anchor, which was developed from stockless anchor; AC-14 HHP Anchor apply to all kinds of seabed(Mud, Soil, Sand, Sandstone, etc.), dig into the seabed quickly and excellent stability, holding-power-to-weight is up to 14.

All AC 14 anchors could be supplied with Classification Certificate, LR, ABS, BV, GL, DNV, KR, NK, IRS and CCS Certificate.

AC-14 HHP Anchor used for shipping or agriculture industry.

AC-14 Anchors Specification:

Material: Casting Steel

Weight: 75KGS to 30000KGS

Finish: Blacking Painting.

Class Certificate: LR, ABS, BV, GL, DNV, KR, NK, IRS and CCS



AC-14 Anchor Weights:

Weight/Mass (KG)	Size(mm)							
	A	B	C	D	E	F	G	J
56KGS	612	298	376	555	109	170	115	24
100KGS	745	364	458	675	130	200	130	28
180KGS	909	442	558	822	162	252	160	36
300KGS	1075	524	660	975	194	298	192	45
428KGS	1213	590	745	1098	215	336	215	48
675KGS	1410	690	868	1278	250	390	255	60
750KGS	1450	700	878	1315	256	396	255	60
910KGS	1560	760	957	1410	273	430	255	60
970KGS	1592	775	978	1445	284	440	280	62
1080KGS	1650	805	1014	1495	294	455	280	62
1305KGS	1760	858	1082	1595	313	485	310	68
1440KGS	1818	885	1118	1645	324	505	310	68

1710KGS	1925	940	1184	1745	343	532	340	74
1845KGS	1975	965	1215	1785	347	546	340	74
2100KGS	2065	1005	1268	1865	354	570	380	82
2475KGS	2175	1062	1340	1970	385	605	385	82
2835KGS	2265	1105	1393	2055	399	625	410	90
3550KGS	2455	198	1508	2225	438	680	415	100
3940KGS	2540	1240	1562	2300	453	705	450	100
4500KGS	2655	1295	1632	2405	473	735	450	100
4840KGS	2720	1330	1670	2465	490	755	480	110
4610KGS	2858	1396	1758	2590	509	790	500	110
6000KGS	2922	1426	1796	2646	515	810	500	110
6900KGS	3062	1496	1884	2775	545	848	540	117
7800KGS	3190	1558	1962	2890	569	884	600	130
8300KGS	3256	1590	2002	2950	574	902	600	130
9300KGS	3382	1652	2080	3064	606	936	630	135
9900KGS	3452	1686	2124	3128	616	956	640	140
10575KGS	3523	1720	2166	3192	628	976	660	145
11100KGS	3589	1720	2166	3192	628	976	660	145
11700KGS	3650	1782	2245	3308	648	1010	680	150
12300KGS	3683	1794	2260	3330	655	1018	700	155
12900KGS	3772	1842	2320	3418	670	1044	700	155
13500KGS	3830	1870	2355	3470	682	1060	730	160
14100KGS	3885	1896	2389	3520	689	1076	730	160
14700KGS	3940	1924	2423	3570	700	1090	730	160
15400KGS	4002	1954	2461	3626	710	1108	730	160
16100KGS	4062	1982	2498	3680	721	1125	770	170
16900KGS	4128	2016	2538	3740	721	1144	700	170
17800KGS	4200	2050	2583	3806	725	1162	800	180
18800KGS	4277	2088	2630	3875	729	1185	800	180
20000KGS	4350	2101	2694	3945	729	1185	820	199
25000KGS	5046	2437	3125	4577	846	1375	848	230

Fast Delivery(Incoterms 2010)

AC-14 HHP Anchor Photo

