

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## HIGH PRESSURE PUMP

# AHP1500 pneumatic hydraulic pump Air-Driven High Pressure Pump

ISO9001 Supplier

Class Certificate

Export Supply

&nbsp;The technical parameters are as follows: &nbsp;OUTPUT PRESSURE(Bar):  
MAX,1500 BAR AT8.0 BAR AIR INPUT. MAX,1050 BAR AT5.5 ...



### Key Highlights

|               |  |
|---------------|--|
| Category      | High Pressure Pump   |
| Standard      | EN   |
| Weight / Size | WEIGHT ( Kg ) 16 KILOS<br>EMPTY DIMENSIOND<br>( mm ) 340*320*380MM AIR<br>ACCESS ... |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR,<br>IRS, RMRS, CCS  |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

|             |   |               |  |
|-------------|---|---------------|--|
| Category    | High Pressure Pump                            | Model / SKU   | AHP1500-pneumatic-hydraulic-pump-Air-Driven-High-Pressure-Pump   |
| Standard    | EN  | Weight / Size | WEIGHT ( Kg ) 16 KILOS<br>EMPTY DIMENSIOND ( mm )<br>340*320*380MM AIR ACCESS<br>PORT 1/2B.S.P.STANDARD<br>INTERNAL THREAD HIGH-<br>VOLTAGE OUTPUT<br>1/4B.S.P.STANDARD INTERNAL<br>THREAD |
| Certificate | ABS, LR, BV, DNVGL, NK, KR,<br>IRS, RMRS, CCS | Warranty      | 12 Months unless specified<br>otherwise  |
| Origin      | China   |               |  |

## The technical parameters are as follows:

|                          |   |
|--------------------------|---|
| OUTPUT PRESSURE(Bar):    | MAX,1500 BAR AT8.0 BAR AIR INPUT.             |
|                          | MAX,1050 BAR AT5.5 BAR AIR INPUT.             |
| TANK CAPACITY ( L ) :    | APPROX.3.5 LITRES.                            |
| PUMPING SPEED:           | APPROX.550 CYCLES/MIN.AT8.0 BAR AIR INPUT.    |
| AIR CONSUMPTION:         | 500 LITRED/MIN.AT 8.0 BAR AIR INPUT.          |
| MAX,FLOW AT NO PRESSURE: | APPROX. 0.35 LITRES/MIN.AT 8.0 BAR AIR INPUT. |
|                          | APPROX. 0.20 LITRES/MIN.AT 5.5 BAR AIR INPUT. |
| DISPLACEMENT PER CYCIE:  | 0.45CM <sup>3</sup> .                         |
| WEIGHT ( Kg )            | 16 KILOS EMPTY                                |
| DIMENSIOND ( mm )        | 340*320*380MM                                 |
| AIR ACCESS PORT          | 1/2B.S.P.STANDARD INTERNAL THREAD             |
| HIGH-VOLTAGE OUTPUT      | 1/4B.S.P.STANDARD INTERNAL THREAD             |