HIGH PRESSURE PUMP

AHP1500 pneumatic hydraulic pump Air-Driven High Pressure Pump

ISO9001 Supplier

Class Certificate

Export Supply

 The technical parameters are as follows: OUTPUT PRESSURE(Bar): MAX,1500 BAR AT8.0 BAR AIR INPUT. MAX,1050 BAR AT5.5 ...



Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	WEIGHT (Kg) 16 KILOS EMPTY DIMENSIOND (mm) 340*320*380MM AIR ACCESS ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	High Pressure Pump	**Model / SKU**	AHP1500-pneumatic-hydraulic-pump-Air-Driven-High-Pressure-Pump
Standard	EN	**Weight / Size**	WEIGHT (Kg) 16 KILOS EMPTY DIMENSIOND (mm) 340*320*380MM AIR ACCESS PORT 1/2B.S.P.STANDARD INTERNAL THREAD HIGH-VOLTAGE OUTPUT 1/4B.S.P.STANDARD INTERNAL THREAD
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

The technical parameters are as follows:

OUTPUT PRESSURE(Bar):	MAX,1500 BAR AT8.0 BAR AIR INPUT.
	MAX,1050 BAR AT5.5 BAR AIR INPUT.
TANK CAPACITY (L) :	APPROX.3.5 LITRES.
PUMPING SPEED:	APPROX.550 CYCLES/MIN.AT8.0 BAR AIR INPUT.
AIR CONSUMPTION:	500 LITRED/MIN.AT 8.0 BAR AIR INPUT.
MAX,FLOW AT NO PRESSURE:	APPROX. 0.35 LITRES/MIN.AT 8.0 BAR AIR INPUT.
	APPROX. 0.20 LITRES/MIN.AT 5.5 BAR AIR INPUT.
DISPLACEMENT PER CYCIE:	0.45CM³.
WEIGHT (Kg)	16 KILOS EMPTY
DIMENSIOND (mm)	340*320*380MM
AIR ACCESS PORT	1/2B.S.P.STANDARD INTERNAL THREAD
HIGH-VOLTAGE OUTPUT	1/4B.S.P.STANDARD INTERNAL THREAD