MARINE COMMUNICATION AND NAVIGATION EQUIPMENT

AIS Antenna

AIS Antenna Frequency: 156-163MHZ SWR:<1.3 Impdedance: 50 ohm Materials: FRP Length: 128.5cm More Antennas:

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Communication And Navigation Equipment
Standard	EN
Material	50 ohm Materials:
Certificate	Mill Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Communication And Navigation Equipment	Model / SKU	AIS-Antenna
Standard	EN	Material	50 ohm Materials:
Certificate	Mill Certificate	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- AIS Antenna
- More Antennas:

AIS Antenna

Frequency: 156-163MHZ

SWR:<1.3

Impdedance: 50 ohm

Materials: FRP

Length: 128.5cm

More Antennas:



▶Marine antenna

GPS Antenna
Frequency: 1575MHZ ±10MHz
Gain: 36dB
SWR: <2.0
Impedance:50 ohm
DC voltage: 3V-5V
Working temperature：-40~85℃
Cable: 7.6m, -3 cable
Polarization: RHCP
Cable connector ： BNC-C-J5 or TNC-J5
Net weight: 440g

AIS Antenna
Frequency: 156-163MHZ
SWR: <1.3
Impedance:50 ohm
Materials: FRP
Length: 128.5 cm

VHF Antenna
Frequency: 140-170MHZ
SWR:<1.5
Gain: 3dB
Impedance:50 ohm
Materials: aluminum jacket
Maximum power: <220W
Length: 127 cm

SSB Antenna(Radio Antenna)
Frequency:1-30MHZ
SWR:<1.5
Mainline: -5 black cable (12m)
Feeder line: -3 white cable (15m)
Net weight:3.3kg

747 Antenna(Intercom)
Frequency: 27-39MHz;
Bandwidth :6MHz

90C Antenna(Intercom)
Frequency: 27-39MHz;
Single row

90C Antenna(Intercom)
Frequency: 27-39MHz;
Double row

Square/round shaped Antenna(Intercom)
Frequency: 27-39MHz; Bandwidth:5MHz