

DIAPHRAGM PUMP

Air Conditioning Pump

Air Conditioning Pump The SEAFLO Magnetic Circulation Pump is a centrifugal magnetic drive pump, eliminating the need for a shaft seal. Pumps are serviceable with a screwdriver. The pump is able t...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Diaphragm Pump
Standard	EN
Weight / Size	1/2"MPT Weight 7.5lbs(3.42Kg) Duty Cycle Continuous Voltage 115V/230V ST...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Diaphragm Pump	Model / SKU	Air-Conditioning-Pump
Standard	EN	Weight / Size	1/2"MPT Weight 7.5lbs(3.42Kg) Duty Cycle Continuous Voltage 115V/230V STANDARD PUMP CONFIGURATIONS Model Voltage Flow Rate Frequency Head Power Amps Draw SFCPA1-G500-01 115 V 8.5 GPM 60 Hz 19 ft / 8.2 psi 115 W 1.8 A 31 LPM 50 Hz 4.3 m 110 W 1.9 A SFCPA2-G500-01 230 V 8.5 GPM 60 Hz 19 ft / 8.2 psi 110 W 0.9 A 31 LPM 50 Hz 4.3 m 105 W 0.9 A
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		



Air Conditioning Pump



The SEAFLO Magnetic Circulation Pump is a centrifugal magnetic drive pump, eliminating the need for a shaft seal. Pumps are serviceable with a screwdriver. The pump is able to be run fully submerged or in open air for complete moisture protection. It also can pump liquids with a specific gravity greater than water, have a higher viscosity.

PUMP	
Liquid	130°F (54°C) Max.
Head	4.3 m
Inlet/Outlet Ports	Inlet: 3/4"FPT Outlet: 1/2"MPT
Weight	7.5lbs(3.42Kg)
Duty Cycle	Continuous
Voltage	115V/230V

STANDARD PUMP CONFIGURATIONS

Model	Voltage	Flow Rate	Frequency	Head	Power	Amps Draw
SFCPA1-G500-01	115 V	8.5 GPM	60 Hz	19 ft / 8.2 psi	115 W	1.8 A
		31 LPM	50 Hz	4.3 m	110 W	1.9 A
SFCPA2-G500-01	230 V	8.5 GPM	60 Hz	19 ft / 8.2 psi	110 W	0.9 A
		31 LPM	50 Hz	4.3 m	105 W	0.9 A