

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE TOOLS

Aluminum-Titanium Drive Hydraulic Wrench

Aluminum-Titanium Drive Hydraulic Wrench Product features: Using aluminum-titanium alloy material, the body is integrally formed, and the strength and toughness of the body are comprehensively strengthe...

ISO9001 Supplier

Class Certificate

Export Supply



jinbomarine.com

Key Highlights

Category	Marine Tools
Standard	ISO
Material	Using aluminum-titanium alloy material, the body is integrally formed, a...
Weight / Size	Model MTH02 MTH05 MTH08 MTH10 MTH16 MTH20 MTH28 MTH36 MTH50 M...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Tools	Model / SKU	Aluminum-Titanium-Drive-Hydraulic-Wrench
Standard	ISO	Material	Using aluminum-titanium alloy material, the body is integrally formed, and the strength and toughness of the body are comprehensively strengthened;
Weight / Size	Model MTH02 MTH05 MTH08 MTH10 MTH16 MTH20 MTH28 MTH36 MTH50 MTH70 Max.torque (Nm) 1882 4466 7451 10732 15339 20108 26392 35397 48740 70660 Min.torque (Nm) 188 447 745 1073 1536 2011 2639 3540 4874 7066 Nut side dimension (mm) 16-36 22-48 27- 55 30-64 36-72 42-90 42-90 48- 100 64-120 90 Drive shaft 3/4" 1" 1-1/2" 1-1/2" 1-1/2" 2-1/2 " 2-1/2 " 2-1/2 " 2-1/2 " 2-1/2" L1(mm) 130 170 202 228 237 273 287 323 351 376 L2(mm) 182 249 286 326 336 391 433 464 494 528 H1(mm) 52 70 81 90 100 110 120 138 153 162 H2(mm) 77 98 125 134 144 164 187 206 217 226 H3(mm) 96 127 149 172 181 206 221 258 279 291 H4(mm) 133 165 184 207 216 241 256 293 315 326 R1(mm) 25.8 34.8 39.8 16.8 50.8 56.8 59.8 70.8 76.8 78.9 R2(mm) 102 140 160 184 192 223 248 256 271 295 Weight (Kg) 1.7 3.8 6.6 9 12.9 24.5 24.5 30.7 44.8 63.2	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Aluminum-Titanium Drive Hydraulic Wrench:

Aluminum-Titanium Drive Hydraulic Wrench

Product features:

Using aluminum-titanium alloy material, the body is integrally formed, and the strength and toughness of the body are comprehensively strengthened;

360°x 180°rotating hose joint, can be used in a small space, adopts precision ratchet, and the output torque accuracy is up to ±3%;

The back stopper prevents the reversal of the tool caused by the torsional rebound of the bolt, and quickly increases the nut locking speed;

The wrench body has an easy-to-operate torque comparison table, and the oil filling hole is beneficial to prevent mechanical wear.

This model can also be changed to a non-stop return lock according to user requirements, which is beneficial to the operation and use of people with different habits;

The lock-type drive shaft can be customized according to user requirements;

Customize various forms of square drive;

The movable handle is easy to move and operate.

Model	MTH02	MTH05	MTH08	MTH10	MTH16	MTH20	MTH28	MTH36	MTH50	MTH70
Max.torque (Nm)	1882	4466	7451	10732	15339	20108	26392	35397	48740	70660
Min.torque (Nm)	188	447	745	1073	1536	2011	2639	3540	4874	7066
Nut side dimension (mm)	16-36	22-48	27-55	30-64	36-72	42-90	42-90	48-100	64-120	90
Drive shaft	3/4"	1"	1-1/2"	1-1/2"	1-1/2"	2-1/2 "	2-1/2 "	2-1/2 "	2-1/2 "	2-1/2"
L1(mm)	130	170	202	228	237	273	287	323	351	376
L2(mm)	182	249	286	326	336	391	433	464	494	528
H1(mm)	52	70	81	90	100	110	120	138	153	162
H2(mm)	77	98	125	134	144	164	187	206	217	226
H3(mm)	96	127	149	172	181	206	221	258	279	291
H4(mm)	133	165	184	207	216	241	256	293	315	326
R1(mm)	25.8	34.8	39.8	16.8	50.8	56.8	59.8	70.8	76.8	78.9
R2(mm)	102	140	160	184	192	223	248	256	271	295
Weight (Kg)	1.7	3.8	6.6	9	12.9	24.5	24.5	30.7	44.8	63.2