

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

KNOWLEDGE

Anchor Selection

Anchor includes anchor head or crown, crown Pin or Stock, Fluke, Shank and Anchor Shackle.

ISO9001 Supplier

Class Certificate

Export Supply

Loading product image...	Key Highlights	
	Category	Knowledge
	Standard	DIN
	Material	The efficiency of an anchor in a given test is expressed in terms of "Ho...
	Weight / Size	Rock or Marl, pool holding ground where an anchors' dead weight is it's ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.		

Technical Specifications			
Category	Knowledge	Model / SKU	Anchor-Selection
Standard	DIN	Material	The efficiency of an anchor in a given test is expressed in terms of "Holding Power" per kg of its own weight, not in "Proof Test" Which indicated physical properties of the material.
Weight / Size	Rock or Marl, pool holding ground where an anchors' dead weight is it's only asset.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

Anchor includes anchor head or crown, crown Pin or Stock, Fluke, Shank and Anchor Shackle.

Optimum design of an anchor is influenced by the specific composition of the ocean floor and categorized into three groups:

1. Mud or silt which varies the most in consistency and offers little resistance to forces.
2. Sand, Ideally the most consistent and where anchors specifically designed reach excellent holding efficiency
3. Rock or Marl, poor holding ground where an anchor's dead weight is its only asset.

The efficiency of an anchor in a given test is expressed in terms of "Holding Power" per kg of its own weight, not in "Proof Test" which indicated physical properties of the material.

The fluke angle of an anchor has a definite effect upon the holding power, the flukes should enter the bottom at an angle that will allow the crown or head to penetrate to a depth which can produce maximum efficiency:

Additionally, it has been determined that:

1. The angle of fluke penetration in mud bottoms should be approximately 50° .
2. In sand the penetration angle should be the area of 30° .
3. For anchoring in various bottoms a compromise approximating 43° is desirable.

Other considerations in selecting an anchor should include:

1. Convenience for handling and stowing
2. Aptitude for taking hold.
3. Physical Strength.
4. Freedom from fouling, which all anchors occasionally do, but some do in lesser degrees.
5. Influence developed by the chain's catenary which absorbs shock loads and lowers the angle of pull at the anchor by its weight

The anchor is the key to effective anchoring or mooring, it is essential to know what to expect from various anchors. The resistance of an anchor to being dragged through a soil has been considered as occurring in two stages:

- a) Biting into the bottom due to the plowing effect of the flukes
- b) Maintain a continuous resistance to drag after it is planted into bottom.

Holding power is directly proportional to projected fluke area and shear strength of the bottom material and inversely proportional to penetration-area resistance. In many cases, a smaller anchor with a favorable fluke area to weight ratio is more dependable than a heavier anchor. Holding Power for the two most widely used anchors are as follows:

1. Stockless Type Anchor, in sand, develop a holding power to weight ratio of seven to one. In Mud they develop three to one, the angle of penetration in both cases is 45 degree.
2. Light Weight Type Anchor, in sand, develop a holding power to weight ratio of twenty to one, with the angle of penetration being 30 degree. In mud they develop nine to one with the angle of penetration being 50 degree.

The depth of penetration in all preceding cases is compiled from three to seven feet in sand and from seventeen to twenty feet in mud. All calculations incorporate a 0° scope angle.