

MARINE LED LIGHT

BAT95-T 80W LED Explosion-proof Light

BAT95-T 80W LED Explosion-proof Light Power:80W Light Effecient>>110lm/W Input Voltage AC220V (85~265V) Frequency 50/60Hz Material 1.high pressure die casting aluminum housing ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine LED Light
Standard	GB
Material	BAT95-T 80W LED Explosion-proof Light Power:80W Light Effecient >110lm/W...
Weight / Size	BAT95-T 80W LED Explosion-proof Light Power:80W Light Effecient >110lm/W...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine LED Light	Model / SKU	BAT95-T-80W-LED-Explosion-proof-Light
Standard	GB	Material	BAT95-T 80W LED Explosion-proof Light Power:80W Light Effecient >110lm/W Input Voltage AC220V (85~265V) Frequency 50/60Hz Material 1.high pressure die casting aluminum housing 2.Stainless steel clamping screw 3.tempered glass cover Led chips : Philips/Cree Working Life : 50000hours Power Factor : PF>0.95 Environment temperature : -20°C~+50°C Explosion-proof marks : Ex de II C T6 Gb IP rating : IP66 Anti-corrosion grade : WF2 Entry:G3/4 introduces mouth specification, suitable ϕ 8mm - ϕ 12mm cable Installation mode:suction top type, wall type, embedded Dimension 330x255x166mm Weight 10kg
Weight / Size	BAT95-T 80W LED Explosion-proof Light Power:80W Light Effecient >110lm/W Input Voltage AC220V (85~265V) Frequency 50/60Hz Material 1.high pressure die casting aluminum housing 2.Stainless steel clamping screw 3.tempered glass cover Led chips : Philips/Cree Working Life : 50000hours Power Factor : PF>0.95 Environment temperature : -20°C~+50°C Explosion-proof marks : Ex de II C T6 Gb IP rating : IP66 Anti-corrosion grade : WF2 Entry:G3/4 introduces mouth specification, suitable ϕ 8mm - ϕ 12mm cable Installation mode:suction top type, wall type, embedded Dimension 330x255x166mm Weight 10kg	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China



0.085402s

China BAT95-T 80W LED Explosion-proof Light:

BAT95-T 80W LED Explosion-proof Light

Power:80W

Light Efficiency >110lm/W

Input Voltage AC220V (85~265V)

Frequency 50/60Hz

Material

- 1.high pressure die casting aluminum housing
 - 2.Stainless steel clamping screw
 - 3.tempered glass cover
- Led chips : Philips/Cree

Working Life : 50000hours

Power Factor : PF>0.95

Environment temperature : -20°C~+50°C

Explosion-proof marks : Ex de II C T6 Gb

IP rating : IP66

Anti-corrosion grade : WF2

Entry:G3/4 introduces mouth specification, suitable ϕ 8mm - ϕ 12mm cable

Installation mode:suction top type, wall type, embedded

Dimension 330x255x166mm

Weight 10kg