

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

STEEL FIRE DOOR WITH WH

BT2094GW Fire steel door(Red colour)

1.60min/90min/180min fire rating
 2. Panic bar, door closer, fireproof handle, stainless steel hinges
 3. Mansonry frame: 16 Gauge(cold roll steel or A60 Galv) 3 hours Warnock Hersey fire label

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Steel fire door with WH
Material	Cold roll steel & Galvanized steel
Certificate	Warnock Hersey, ITS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Steel fire door with WH	Model / SKU	BT2094GW-Fire-steel-door-Red-colour
Material	Cold roll steel & Galvanized steel	Certificate	Warnock Hersey, ITS
Warranty	12 Months unless specified otherwise	Origin	China

China BT2094GW Fire steel door(Red colour):

BT2094GW Red colour

1.60min/90min/180min fire rating

2. Panic bar, door closer, fireproof handle, stainless steel hinges, fire proof glass

3. Mansonry frame: 16 Gauge(cold roll steel or A60 Galv)

3 hours Warnock Hersey fire label



Hollow Metal Door & Frame

(Fire Rating up to 3 hours & Positive Pressure)
MECHANICALLY INTERLOCK SEAM, LAP SEAM, STITCHED SEAM AVAILABLE

Best Option For Commercial / Institutional / Industrial Entrances

Door Specs.

- Standard One Saver Option:**
 - 18 Gauge
 - 20 Gauge
 - 22 Gauge
 - 24 Gauge
 - 26 Gauge
 - 28 Gauge
 - 30 Gauge
 - 32 Gauge
 - 34 Gauge
 - 36 Gauge
 - 38 Gauge
 - 40 Gauge
- Special Options:**
 - 18 Gauge
 - 20 Gauge
 - 22 Gauge
 - 24 Gauge
 - 26 Gauge
 - 28 Gauge
 - 30 Gauge
 - 32 Gauge
 - 34 Gauge
 - 36 Gauge
 - 38 Gauge
 - 40 Gauge

Hollow Metal Door & Frame

(Fire Rating up to 3 hours & Positive Pressure)

EMTRADA

Frame Specs.

- DRYWALL FRAMES:**
 - 18 Gauge
 - 20 Gauge
 - 22 Gauge
 - 24 Gauge
 - 26 Gauge
 - 28 Gauge
 - 30 Gauge
 - 32 Gauge
 - 34 Gauge
 - 36 Gauge
 - 38 Gauge
 - 40 Gauge
- MASONRY FRAMES:**
 - 18 Gauge
 - 20 Gauge
 - 22 Gauge
 - 24 Gauge
 - 26 Gauge
 - 28 Gauge
 - 30 Gauge
 - 32 Gauge
 - 34 Gauge
 - 36 Gauge
 - 38 Gauge
 - 40 Gauge
- DOUBLE-EGRESS:**
 - 18 Gauge
 - 20 Gauge
 - 22 Gauge
 - 24 Gauge
 - 26 Gauge
 - 28 Gauge
 - 30 Gauge
 - 32 Gauge
 - 34 Gauge
 - 36 Gauge
 - 38 Gauge
 - 40 Gauge

All the products information just for your reference only subject to our available products

LISTING REPORT - MANUFACTURING
Issued: Jul 17 2006 5:38PM

Inspection Tests And Evaluation Of

Mexin Series 1200, 1600, 1800 3-Hour Polystyrene Core Steel Fire Door (13901)

RENDERED TO
Chongqing Mexin Messon Doors Industry Co., Ltd.
No. 51 Baihe Road
Chongqing,
CHINA

GENERAL: This Report gives the results of the inspection, tests and evaluation of the above for compliance with applicable requirements of the following standards: ASTM E152-81a UL 10(c) (1998) UBC 7-2 (1997) UBC 7-2 (1994) UL 10(b) (1997) ASTM E2074 (2000) NFPA 252 (2003) CAN / ULC S104 1980 R1985

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. To verify a listing, call 888-347-3473, or check our searchable online Directory of Listed Products at www.intertek.com.