

JIS NEEDLE VALVE

Brass Needle Angle Valve with Ring Joint Nut at Outlet

ISO9001 Supplier

Class Certificate

Export Supply

Brass Needle Valve is used to connect the copper tubing, control the flow of liquids or gas requiring close regulating. Made of brass rods and brass except for "O" rings. Technical Specification: 1. Applicabl...



Key Highlights

Category	JIS Needle Valve
Standard	EN
Material	Brass
Weight / Size	3.43Mpa (35kgf/cm2) 3.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	JIS Needle Valve	Model / SKU	Brass-Needle-Angle-Valve-with-Ring-Joint-Nut-at-Outlet
Standard	EN	Material	Brass
Weight / Size	3.43Mpa (35kgf/cm2) 3.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Brass Needle Angle Valve with Ring Joint Nut at Outlet:
- Main Size(mm):
- Technical Specification:

China Brass Needle Angle Valve with Ring Joint Nut at Outlet:

Brass Needle Valve is used to connect the copper tubing, control the flow of liquids or gas requiring close regulating. Made of brass rods and brass except for "O" rings.



Technical Specification:

1. Applicable temperature will be -20°C to 100°C
2. Max Pressure: 3.43Mpa (35kgf/cm²)
3. Recommended for use at less than 80% of max load pressure at temperature between 80°C and 100°C.

Main Size(mm):

IMPA	Nominal Size	OD of Tube	Thread		Height	Length
			Ring Joint Side	Male Thread		
752116	6 x 1/8	6	PF-1/4	PT-1/8	55	27
752117	6 x 1/4	6	PF-1/4	PT-1/4	58	27
752118	8 x 1/4	8	PF-3/8	PT-1/4	65	28
752119	10 x 3/8	10	PF-3/8	PT-3/8	73	34
752120	12 x 1/2	12	PF-1/2	PT-1/2	76	38
752121	14 x 1/2	14	PF-1/2	PT-1/2	76	40