

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

CB MARINE STORM VALVE

Bronze Screw Down Vertical Storm Valve CB/T3477-92 Type A/AS

Marine Screw Down Vertical Storm Valve CB/T3477 is the ship side valve to discharge sewage or waste water and prevent outboard water pouring. It is can closed by the handwheel. Technical Specification: Design ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	CB Marine Storm Valve
Standard	GB
Material	Bronze
Weight / Size	GB600 Type A- Straight Type, Flange size as per GB569 Type AS-Straight T...
Certificate	CCS, BV, ABS, GL, LR, DNV, NK, RINA, KR, IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	CB Marine Storm Valve	Model / SKU	Bronze-Screw-Down-Vertical-Storm-Valve-CB-T3477-92-Type-A-AS
Standard	GB	Material	Bronze
Weight / Size	GB600 Type A- Straight Type, Flange size as per GB569 Type AS-Straight Type, Flange size as per GB2501 Type B- Angle Type, Flange size as per GB569 Type BS-Angle Type, Flange size as per GB2501 Type Nominal Pressure (Mpa) Nominal Size (mm) Applicable medium A,AS,B,BS 0.5 50-150 sea water, fresh water & sewage Main Parts & Material:	Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> ■ China Bronze Screw Down Vertical Storm Valve CB/T3477-92 Type A/AS: ■ Main Parts & Material: 	<ul style="list-style-type: none"> ■ Technical Specification: ■ Main Size List(mm):
-----------------	---	---

China Bronze Screw Down Vertical Storm Valve CB/T3477-92 Type A/AS:



Marine Screw Down Vertical Storm Valve CB/T3477 is the ship side valve to discharge sewage or waste water and prevent outboard water pouring. It can be closed by the handwheel.

Technical Specification:

Design Standard: CB/T3477-92

Test Standard: GB600

Type A- Straight Type, Flange size as per GB569

Type AS-Straight Type, Flange size as per GB2501

Type B- Angle Type, Flange size as per GB569

Type BS-Angle Type, Flange size as per GB2501

Type	Nominal Pressure (Mpa)	Nominal Size (mm)	Applicable medium
A,AS,B,BS	0.5	50-150	sea water, fresh water & sewage



Main Parts & Material:

Body- Bronze

Bonnet- Bronze

Disc-Brnze

Stem-Bronze

Clamp Material-Brass

Main Size List(mm):

Type A,B:

nominal diameter	structure dimension							Thickness δ		flange connection dimension					bolt		hand wheel		Lift Range m	Weight(kg)			
	H	H1	H2	H3	L	L1	L2	cast steel	bronze	D	D1	D2	b	d0	n	Th	Do	S		cast steel		bronze	
																				A	B	A	B
50	210	170	300	327	135	930	1000	7.5	5	135	130	84	130	135	6	M14	80	110	40	12	13	10	11
65	240	200	385	342	144	1110	1200	8.0	6	155	150	110	140	145	6	M14	80	110	45	17	19	13	15
80	260	220	400	370	155	1220	1400	8.5	6	170	165	118	140	145	8	M14	80	110	45	22	24	19	21
100	280	240	430	399	172	1330	1530	9.0	6	190	185	138	140	145	8	M14	80	110	45	30	35	28	31
125	330	270	465	430	195	1560	1800	10.0	7	215	210	166	140	145	10	M14	80	110	65	44	50	40	46
150	360	300	490	457	213	1670	1910	11.0	7	240	235	174	140	145	12	M14	120	110	65	52	67	48	63

Type AS/BS:

nominal diameter	structure dimension							Thickness δ		flange connection dimension					bolt		hand wheel		Lift Range m	Weight(kg)			
	H	H1	H2	H3	L	L1	L2	cast steel	bronze	D	D1	D2	b	d0	n	Th	Do	S		cast steel		bronze	
																				AS	BS	AS	BS



50	2 1 0	1 7 0	3 6 0	3 2 7	1 3 5	9 0 0	1 0 0	8.0	5	1 4 0	11 0 0	9 0 0	1 6 4	1 4 4	M 12	80	1 1	40	1 2	1 3	1 1	1 2
65	2 4 0	2 0 0	3 8 5	3 4 2	1 4 2	1 1 0	1 1 0	8.0	6	1 6 0	1 3 0	11 0 0	1 6 4	1 4 4	M 12	80	1 1	45	1 7	1 9	1 4	1 6
80	2 6 0	2 2 0	4 0 0	3 7 0	1 5 5	1 2 0	1 2 0	9.0	6	1 9 0	1 5 0	1 2 8	1 8 8	1 8 8	M 16	80	1 1	45	2 2	2 4	2 0	2 2
100	2 8 0	2 5 0	4 3 0	3 9 3	1 7 2	1 3 0	1 3 7	9.0	6	2 1 0	1 7 0	1 4 8	1 8 8	1 8 8	M 16	80	1 1	45	3 0	3 5	2 9	3 3
125	3 3 0	2 7 0	4 6 5	4 0 7	1 9 5	1 5 0	1 6 0	10.0	7	2 4 0	2 0 0	1 7 8	2 0 8	1 8 8	M 16	80	1 1	65	4 4	5 0	4 2	4 8
150	3 6 0	3 1 0	4 9 0	4 3 7	2 1 3	1 6 5	1 7 4	10.0	7	2 6 5	2 2 5	2 0 2	2 0 8	1 8 8	M 16	12 0	1 1	65	5 2	6 7	5 0	6 4

