


**MARINE FIRE DOOR LOCK**

# C-2B Fire Protection Vessel Door Lock

This vessel door lock incorporates double bolt, single cylinder and master key mechanism, lock body width of 80mm. The bolt may be operated freely by lever handle at ordinary time. The dead bolt can be unlocked...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

<b>Category</b>	Marine Fire Door Lock
<b>Standard</b>	DIN
<b>Material</b>	Suitable for steel or watertight doors about 40 mm in thickness.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Marine Fire Door Lock	<b>Model / SKU</b>	C-2B-Fire-Protection-Vessel-Door-Lock
<b>Standard</b>	DIN	<b>Material</b>	Suitable for steel or watertight doors about 40 mm in thickness.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

## China C-2B Fire Protection Vessel Door Lock:

This vessel door lock incorporates double bolt, single cylinder and master key mechanism, lock body width of 80mm. The bolt

may be operated freely by lever handle at ordinary time. The dead bolt can be unlocked by knob inside, and locked or unlocked

by keys outside. Water—proof cover can be used.

Suitable for steel or watertight doors about 40 mm in thickness.



