

SHIPBUILDING STEEL

C Type Hydraulic Press For Shipyard

C Type Hydraulic Press

The machine is applicable to axial parts, profile calibration process, the axis and set workpieces'press mounting, even the simple plank parts to stretching, bending, stamping, molding, and dropping material and so on, also can pressure the general powder, plastic products.



Key Highlights

| | |
|---------------|--|
| Category | Shipbuilding Steel |
| Standard | DIN |
| Material | C Type Hydraulic Press The machine is applicable to axial parts, profil... |
| Weight / Size | Machine working environment 1) Temperature 0°C ~ 40°C 2) Humidity relati... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

| | | | |
|---------------|---|-------------|--|
| Category | Shipbuilding Steel | Model / SKU | C-Type-Hydraulic-Press-For-Shipyard |
| Standard | DIN | Material | C Type Hydraulic Press The machine is applicable to axial parts, profile calibration process, the axis and set workpieces'press mounting, even the simple plank parts to stretching, bending, stamping, molding, and dropping material and so on, also can pressure the general powder, plastic products. |
| Weight / Size | Machine working environment 1) Temperature 0°C ~ 40°C 2) Humidity relative temperature below 90% 3) Voltage three phase 380 V (-15%, +15%) 50 Hz C Type Hydraulic Press Technical Specifications name 6.3 10 16 25 40 63 100 160 pressure KN 63 100 160 250 400 630 1000 1600 2000 3150 4000 5000 6300 8000 Max pressure Mpa 8 12.5 20 16 25 25 25 25 25 25 25 25 25 25 25 Block trave mm 250 250 400 400 400 500 600 700 700 800 800 900 900 900 Opening mouth mm 400 400 500 630 630 750 800 900 1000 1100 1250 1300 1500 1500 throat depth mm 200 200 250 350 350 320 400 420 450 800 1500 1500 1500 1500 1500 Block speed empty mm/s 80 80 120 100 80 working mm/s 18~20 20~22 18~20 18~20 18~20 18~20 15~20 10~12 return mm/s 55 50 50 75 75 100 100 100 Working table dimensions L-R mm 440 440 500 580 700 710 800 800 mm 380 380 450 570 570 600 700 700 Table height over the ground mm 700 700 710 710 710 810 800 800 900 400 400 400 400 400 Hole dimension mm φ100 φ100 φ100 Main power KW 3 3 4 5.5 5.5 7.5 7.5 7.5 15 22 22 2x22 2x22 2x22 | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin | China |

CONTENTS

- C Type Hydraulic Press

- C Type Hydraulic Press Technical Specifications

C Type Hydraulic Press

The machine is applicable to axial parts, profile calibration process, the axis and set workpieces'press mounting, even the simple plank parts to stretching, bending, stamping, molding, and dropping material and so on, also can pressure the general powder, plastic products.

Machine working environment

- 1) Temperature 0°C ~ 40°C
- 2) Humidity relative temperature below 90%
- 3) Voltage three phase 380 V (-15%, +15%) 50 Hz

C Type Hydraulic Press Technical Specifications

| | | | | | | | | | | | | | | | | | |
|------------------------------|---------|------|-------|-------|-----|-------|-----|-------|------|-------|------|-------|------|-------|------|-------|--|
| name | | 6.3 | | 10 | | 16 | | 25 | | 40 | | 63 | | 100 | | 160 | |
| pressure | KN | 63 | 100 | 160 | | 250 | 400 | 630 | 1000 | 1600 | 2000 | 3150 | 4000 | 5000 | 6300 | 8000 | |
| Max pressure | Mpa | 8 | 12.5 | 20 | | 16 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | |
| Block trave | mm | 250 | 250 | 400 | | 400 | 400 | 500 | 600 | 700 | 700 | 800 | 800 | 900 | 900 | 900 | |
| Opening mouth | mm | 400 | 400 | 500 | | 630 | 630 | 750 | 800 | 900 | 1000 | 1100 | 1250 | 1300 | 1500 | 1500 | |
| throat depth | mm | 200 | 200 | 250 | | 350 | 350 | 320 | 400 | 420 | 450 | 800 | 1500 | 1500 | 1500 | 1500 | |
| Block speed | empty | mm/s | 80 | | 80 | | 120 | | 100 | | 80 | | | | | | |
| | working | mm/s | 18~20 | 20~22 | | 18~20 | | 18~20 | | 18~20 | | 18~20 | | 15~20 | | 10~12 | |
| | return | mm/s | 55 | 50 | | 50 | | 75 | | 75 | | 100 | | 100 | | 100 | |
| Working table dimensions | L-R | mm | 440 | 440 | | 500 | | 580 | | 700 | | 710 | | 800 | | 800 | |
| | mm | 380 | 380 | | 450 | | 570 | | 570 | | 600 | | 700 | | 700 | | |
| Table height over the ground | mm | 700 | 700 | 710 | 710 | 710 | 810 | 800 | 800 | 900 | 400 | 400 | 400 | 400 | 400 | 400 | |
| Hole dimension | mm | φ100 | φ100 | φ100 | | | | | | | | | | | | | |
| Main power | KW | 3 | 3 | 4 | 5.5 | 5.5 | 7.5 | 7.5 | 7.5 | 15 | 22 | 22 | 2x22 | 2x22 | 2x22 | | |