

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE LED LIGHT

CCD5-2QL LED Pendant Light

Application Applied to illumination of water dripping, water spattering, water coagulating place in military ship and ship, such as dry cabin, deck, outer and weather deck etc. Product

Feature 1. Shel...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

| | |
|---------------|---|
| Category | Marine LED Light |
| Standard | GB |
| Material | Shell uses good quality steel plate. |
| Weight / Size | Specification Type LED Type Voltage Power LED Power Lamp Holder Materi... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



| Technical Specifications | | | |
|--------------------------|--|--------------------|---|
| Category | Marine LED Light | Model / SKU | CCD5-2QL-LED-Pendant-Light |
| Standard | GB | Material | Shell uses good quality steel plate. |
| Weight / Size | <p>Specification Type LED Type Voltage Power LED Power Lamp Holder Material Color Weight CCD1-2 CCD1-2QL 24-240V 60W <=10W E27 Steel Clear,Green,Red 1.6kg CCD2-1 CCD2-1QL 24-240V 40W <=10W E27 Aluminum Clear 2.5kg CCD4- 1 CCD4-1QL 24-240V 60W <=10W E27 Aluminum Clear 2.3kg CCD5-2 CCD5-2QL 24- 240V 25W <=5W B15d Brass, Plastic Clear 0.5kg CCD9-5 CCD9-5QL 24-240V 60W <=10W E27 Brass Clear,Green,Red, Yellow, Blue 2.5kg CCD9-5A CCD9-5AQL 24- 240V 25W <=5W B15d Brass 2.4kg CCD9-6 CCD9-6QL 24- 240V 60W <=10W E27 Brass 4.2kg CCD9-6A CCD9-6AQL 24- 240V 25W <=5W B15d Brass 4.1kg CCD9-8 CCD9-8QL 24- 240V 60W <=10W E27 Brass 1.2kg CCD15-2 CCD15-2QL 24- 240V 60W <=10W E27 Brass 2.3kg CCD15-2A CCD15-2AQL 24-240V 25W <=5W B15d Brass 2.2kg WB-1 WB-1QL 24-240V 15W <=5W B15d Synthetic Clear 0.71kg WB-2B WB-2BQL 24-240V 60W <=10W E27 Synthetic Clear 0.85kg DS7-1M DS7-1MQL 24- 240V 15W <=5W B15d Synthetic Clear 0.74kg DS7-2M DS7-2MQL 24-240V 60W <=10W E27 Synthetic Clear 0.95kg CCD9- 5QL LED Pendant Light CCD9- 6QL LED Pendant Light</p> | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin | China |

China CCD5-2QL LED Pendant Light:

Application



Applied to illumination of water dripping, water spattering, water coagulating place in military ship and ship, such as dry cabin, deck, outer and weather deck etc.


Product Feature

1. Shell uses good quality steel plate.
2. Lampshade uses injection of AS with metal guard.
3. LED Light Source, light soft, no glare, supper high uniformity and visual comfort, color \geq 80%, light rate $>$ 70%, life time 30000h,energy saving 50%, new green environmental product, easy installation, general G12 lamp holder.
4. Environment temperature I s -20-40degree within the scope of work.
5. Protection class is IP56.
6. Outdoor light should e use stainless steel body.

Standard

1. Chapter 3, Part 4 of Classification Society Rules for Classification of Sea-going Steel Ships 2015 and its Amendments;
- 2.GB7000.1-2015 , Luminaires –Part1:General requirements and tests.

Specification

| Type | LED Type | Voltage | Power | LED Power | Lamp Holder | Material | Color | Weight |
|----------|------------|---------|-------|------------|-------------|----------------|-----------------------------|---|
| CCD1-2 | CCD1-2QL | 24-240V | 60W | \leq 10W | E27 | Steel | Clear,Green,Red | 1.6kg |
| CCD2-1 | CCD2-1QL | 24-240V | 40W | \leq 10W | E27 | Aluminum | Clear | 2.5kg |
| CCD4-1 | CCD4-1QL | 24-240V | 60W | \leq 10W | E27 | Aluminum | Clear | 2.3kg |
| CCD5-2 | CCD5-2QL | 24-240V | 25W | \leq 5W | B15d | Brass, Plastic | Clear | 0.5kg |
| CCD9-5 | CCD9-5QL | 24-240V | 60W | \leq 10W | E27 | Brass | Clear,Green,Red,Yellow,Blue | 2.5kg |
| CCD9-5A | CCD9-5AQL | 24-240V | 25W | \leq 5W | B15d | Brass | | 2.4kg |
| CCD9-6 | CCD9-6QL | 24-240V | 60W | \leq 10W | E27 | Brass | | 4.2kg |
| CCD9-6A | CCD9-6AQL | 24-240V | 25W | \leq 5W | B15d | Brass | | 4.1kg |
| CCD9-8 | CCD9-8QL | 24-240V | 60W | \leq 10W | E27 | Brass | | 1.2kg |
| CCD15-2 | CCD15-2QL | 24-240V | 60W | \leq 10W | E27 | Brass | | 2.3kg |
| CCD15-2A | CCD15-2AQL | 24-240V | 25W | \leq 5W | B15d | Brass | | 2.2kg |
| WB-1 | WB-1QL | 24-240V | 15W | \leq 5W | B15d | Synthetic | | Clear |
| WB-2B | WB-2BQL | 24-240V | 60W | \leq 10W | E27 | Synthetic | Clear | 0.85kg |
| DS7-1M | DS7-1MQL | 24-240V | 15W | \leq 5W | B15d | Synthetic | Clear | 0.74kg |
| DS7-2M | DS7-2MQL | 24-240V | 60W | \leq 10W | E27 | Synthetic | Clear |  0.058104s |

CCD9-5QL LED Pendant Light



CCD9-6QL LED Pendant Light

