

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE GENERATOR

# CCFJ30J-W 30-90KW Cummins Series Diesel Generator Set

ISO9001 Supplier

Class Certificate

Export Supply

Cummins series diesel generator set: Dongfeng Cummins diesel generator set to choose Dongfeng Cummins B, C, L series diesel engine with Stamford motor, marathon, Siemens, three wave generator can be selected, such...



## Key Highlights

Category	Marine Generator
Standard	EN
Material	24 v (DV), Using alloy steel forging crankshaft journal induction harden...
Weight / Size	25% less than other brand engine parts, reduces the volume and weight of...
Certificate	CCS, BV, ABS, GL , LR, NK

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Marine Generator	<b>Model / SKU</b>	CCFJ30J-W-30-90KW-Cummins-Series-Diesel-Generator-Set
<b>Standard</b>	EN	<b>Material</b>	24 v (DV), Using alloy steel forging crankshaft journal induction hardening, Most is equipped with the company unique PT fuel system except (B, C series) Rotary engine oil, diesel oil and water filter, dry type air filter.
<b>Weight / Size</b>	25% less than other brand engine parts, reduces the volume and weight of the diesel engine, Fuel oil and engine oil channel most drill within the cylinder block and cylinder head, Stable performance, low failure rate and maintenance cost, Control system working voltage:	<b>Certificate</b>	CCS, BV, ABS, GL , LR, NK
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

**CONTENTS**

- Cummins series diesel generator set:

- Dongfeng Cummins series of advantages:

## Cummins series diesel generator set:

Dongfeng Cummins diesel generator set to choose Dongfeng Cummins B, C, L series diesel engine with Stamford motor, marathon, Siemens, three wave generator can be selected, such as high reliability, easy maintenance, low fuel consumption, low noise, large power output, continuous operation time, global 3 packets of group, etc. As a joint venture of China and the United States Cummins engine industry's biggest foreign investors in China, China has the Dongfeng Cummins engine co., LTD (produce B, C and L series) and Chongqing Cummins engine co., LTD. (production of N and K series), and other manufacturing enterprises, and to Cummins global unified quality standard production. Using electronic governor, the cooling water temperature is too high, low oil pressure and speed alarm and protection functions such as automatic parking. Cummins company's global service network, to provide customers with reliable service.

## Dongfeng Cummins series of advantages:

25% less than other brand engine parts, reduces the volume and weight of the diesel engine,  
 Fuel oil and engine oil channel most drill within the cylinder block and cylinder head,  
 Stable performance, low failure rate and maintenance cost,  
 Control system working voltage: 24 v (DV),  
 Using alloy steel forging crankshaft journal induction hardening,  
 Most is equipped with the company unique PT fuel system except (B, C series)  
 Rotary engine oil, diesel oil and water filter, dry type air filter.



Generating set specifications				Diesel Engine Specifications						generator specifications		Size	
model	Rated power		Voltage/frequency Hz/v	Model	RPM	Number of Cylinders	Diameter of cylinder/Stroke(mm)	displacement (L)	fuel consumption (g/kw.h)	Model		L*W*H (mm)	Weight (kg)
	KW	KVA								Stanford	marathon		
CCFJ30J-W	30	37.5	50/400	4BTA3.9-GM47	1500	4L	102/120	3.9	210	UCM224C	MP-H-30-4	1670*850*1270	800
CCFJ40J-W	40	50	50/400	4BTA3.9-GM47	1500	4L	102/120	3.9	210	UCM224E	MP-H-40-4	1760*850*1270	800
CCFJ50J-W	50	63	50/400	6BT5.9-GM83	1500	4L	102/120	5.9	206	UCM224F	MP-H-50-4	1980*895*1300	850
CCFJ64J-W	64	80	50/400	6BT5.9-GM83	1500	6L	102/120	5.9	206	UCM274C	MP-H-64-4	1980*900*1300	1000
CCFJ75J-W	75	93.8	50/400	6BT5.9-GM83	1500	6L	102/120	5.9	206	UCM274D	MP-H-75-4	1980*895*1300	1250
CCFJ90J-W	90	113	50/400	6BTA5.9-GM100	1500	6L	102/120	5.9	206	UCM274E	MP-H-90-4	2080*895*1300	1300