

LIFEBOAT AND RESCUE BOAT ACCESSORIES

CD4212-2 Lifeboat Battery Charger

The charger is specially designed for maintenace charging of batteries used in lifeboats.
 Supply voltage: 42V/AC 50/60HZ Fully Charged voltage: 14.4VDC Complementary voltage: 13.3VDC Charing cur...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

| | |
|----------------------|---|
| Category | Lifeboat And Rescue Boat Accessories |
| Standard | EN |
| Weight / Size | 13.3VDC Charing current:≤3A(2 pieces of batteries) Dimension: |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications | | | |
|--------------------------|--|----------------------|---|
| Category | Lifeboat And Rescue Boat Accessories | Model / SKU | CD4212-2-Lifeboat-Battery-Charger |
| Standard | EN | Weight / Size | 13.3VDC Charing current:≤3A(2 pieces of batteries) Dimension: |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty | 12 Months unless specified otherwise |
| Origin | China | | |

China CD4212-2 Lifeboat Battery Charger:

The charger is specially designed for maintenace charging of batteries used in lifeboats.

Supply voltage: 42V/AC 50/60HZ

Fully Charged voltage: 14.4VDC

Complementary voltage: 13.3VDC

Charing current:≤3A(2 pieces of batteries)



Dimension: 243x134x80mm

Weight:5kgs

Protection grade:IP56

Temperature:-25 to 55 centigrade.

Use Method: Connect in proper order, connect the battery, then connect the power source : 42C/AC

