

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

IEC 60092 STANDARD CABLE (CHINA TYPE)

CEPF/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(No Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CEPF/SC Marine Power & Lighting Cable 0.6/1KV Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 Insulation : EPR Insulation Inner Covering: None ...




Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/EPR insulation/Halogen-free Thermoplastic Polyolefin sheat...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CEPF-SC-Flame-Retardant-Marine-Power-Lighting-Cable-0-6-1KV-No-Armoured
Standard	EN	Material	Tinned Copper/EPR insulation/Halogen-free Thermoplastic Polyolefin sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China



CONTENTS

- China CEPF/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(No Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application

China CEPF/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(No Armoured):



CEPF/SC Marine Power & Lighting Cable 0.6/1KV

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Inner Covering: None

Armour : None

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A


Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300



Feature

Halogen-free, Low Smoke, Flame retardant

Application

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.