


IEC 60092 STANDARD CABLE (CHINA TYPE)

# CEPF86/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured)

- ISO9001 Supplier
- Class Certificate
- Export Supply

CEPF86/SC Marine Cable is tinned copper wire braided and Flame Retardant Marine(Shipboard) Power & Control Cable. Cable Construction &nbsp; Conductor: Tinned Copper. IEC 60228 Class 2...




### Key Highlights

<b>Category</b>	IEC 60092 Standard Cable (China Type)
<b>Standard</b>	EN
<b>Material</b>	Tinned Copper/EPR insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF1
<b>Weight / Size</b>	IEC 61034-1, IEC61034-2 Cores & Size Cores:
<b>Certificate</b>	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	IEC 60092 Standard Cable (China Type)	<b>Model / SKU</b>	CEPF86-SC-Flame-Retardant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
<b>Standard</b>	EN	<b>Material</b>	Tinned Copper/EPR insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF1
<b>Weight / Size</b>	IEC 61034-1, IEC61034-2 Cores & Size Cores:	<b>Certificate</b>	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China



**CONTENTS**

- China CEPF86/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

## China CEPF86/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CEPF86/SC Marine Cable is tinned copper wire braided and Flame Retardant Marine(Shipboard) Power & Control Cable.

### Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoplastic

Armour : Copper Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

### Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

### Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300



## **Feature**

Halogen-free, Low Smoke, Flame retardant

## **Application:**

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.

