

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

IEC 60092 STANDARD CABLE (CHINA TYPE)

CEPJ85/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CEPJ85/SC is tinned copper wire braided and Flame Retardant Marine Cable. Cable Construction ; Conductor: Tinned Copper. IEC 60228 Class 2 Insulation ; EPR Insulati...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/EPR insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CEPJ85-SC-Flame-Retardant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
Standard	EN	Material	Tinned Copper/EPR insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China



0.045892s

CONTENTS

- China CEPJ85/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CEPJ85/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CEPJ85/SC is tinned copper wire braided and Flame Retardant Marine Cable.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoset Polyolefin(SHF2)

Armour : Copper Wire Braided

Outer Sheath : Halogen-free Thermoset Polyolefin(SHF2)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A


Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300



Feature

Halogen-free, Low Smoke, Flame retardant

Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.

