IEC 60092 STANDARD CABLE (CHINA TYPE)

# CEPJ85/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CEPJ85/SC is tinned copper wire braided and Flame Retardant Marine Cable. Cable Construction   Conductor: Tinned Copper. IEC 60228 Class 2 Insulation : EPR Insulati...




## Key Highlights

| | |
|---|---|
| **Category** | IEC 60092 Standard Cable (China Type) |
| **Standard** | EN |
| **Material** | Tinned Copper/EPR insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2... |
| **Weight / Size** | IEC 61034-1, IEC61034-2 Cores & Size Cores: |
| **Certificate** | ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | IEC 60092 Standard Cable (China Type) | **Model / SKU** | CEPJ85-SC-Flame-Retardant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured |
| **Standard** | EN | **Material** | Tinned Copper/EPR insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2 Outer Sheath |
| **Weight / Size** | IEC 61034-1, IEC61034-2 Cores & Size Cores: | **Certificate** | ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS |
| **Warranty** | 12 Months unless specified otherwise | **Origin** | China |

CONTENTS


- China CEPJ85/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:


## China CEPJ85/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):




CEPJ85/SC is tinned copper wire braided and Flame Retardant Marine Cable.

## Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoset Polyolefin(SHF2)

Armour : Copper Wire Braided

Outer Sheath : Halogen-free Thermoset Polyolefin(SHF2)

## Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

## Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5. 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300

## Feature

Halogen-free, Low Smoke, Flame retardant

## Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.