IEC 60092 STANDARD CABLE (CHINA TYPE)

CEPJ95/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CEPJ95/NC is galvanized steel wire braided and Fire Resistant Marine Power and Control Cable, 0.6/1kv. Cable Construction   Conductor: Tinned Copper. IEC 60228 Class 2 Mic...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/Mica Tape/EPR insulation/SHF2 sheath/Galvanized Steel Wire...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	IEC 60092 Standard Cable (China Type)	**Model / SKU**	CEPJ95-NC-Fire-Resistant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
Standard	EN	**Material**	Tinned Copper/Mica Tape/EPR insulation/SHF2 sheath/Galvanized Steel Wire Braided/SHF2
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	**Surface**	galvanized
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China CEPJ95/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CEPJ95/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CEPJ95/NC is galvanized steel wire braided and Fire Resistant Marine Power and Control Cable, 0.6/1kv.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Galvanized Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Fire Resistant: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5. 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300

Feature

Halogen-free, Low Smoke, Fire-resistant.

Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.