

Jinbo Marine

Marine & Offshore Equipment Datasheet


PRODUCT DATASHEET

IEC 60092 STANDARD CABLE (CHINA TYPE)

CEPJ95/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured)

- ISO9001 Supplier
- Class Certificate
- Export Supply

CEPJ95/NC is galvanized steel wire braided and Fire Resistant Marine Power and Control Cable, 0.6/1kv. Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 Mic...

	Key Highlights	
	Category	IEC 60092 Standard Cable (China Type)
	Standard	EN
	Material	Tinned Copper/Mica Tape/EPR insulation/SHF2 sheath/Galvanized Steel Wire...
	Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS	
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.		



Technical Specifications			
Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CEPJ95-NC-Fire-Resistant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
Standard	EN	Material	Tinned Copper/Mica Tape/EPR insulation/SHF2 sheath/Galvanized Steel Wire Braided/SHF2
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Surface	galvanized
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China CEPJ95/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):	■ Cable Construction
	■ Standards	■ Cores & Size
	■ Feature	■ Application:

China CEPJ95/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CEPJ95/NC is galvanized steel wire braided and Fire Resistant Marine Power and Control Cable, 0.6/1kv.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)



Armour : Galvanized Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Fire Resistant: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300

Feature

Halogen-free, Low Smoke, Fire-resistant.

Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.