

ACTUATOR SERIES

# CG-HA Hydraulic Actuator

Hydraulic actuator with high accuracy, fast response, and can achieve high precision control, the transmission is stable and reliable, and the travel regulation is accurate, low speed large torque transmission without spe...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Actuator Series
Standard	ISO
Weight / Size	90±5 degree Ambient temperature:-20 °C to 80 °C Outside Dimension Of CG-HA...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Actuator Series	Model / SKU	CG-HA-Hydraulic-Actuator
Standard	ISO	Weight / Size	90±5 degree Ambient temperature:-20 °C to 80 °C Outside Dimension Of CG-HA Hydraulic Actuator:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

**CONTENTS**

- China CG-HA Hydraulic Actuator:
- Technical Specification:
- Outside Dimension Of CG-HA Hydraulic Actuator:

## China CG-HA Hydraulic Actuator:

Hydraulic actuator with high accuracy, fast response, and can achieve high precision control, the transmission is stable and reliable, and the travel regulation is accurate, low speed large torque transmission without speed reduction device, actuator for controlling the 0 degree to 90 degree rotary valves and other products, such as butterfly valve, ball

valves, air door, flapper valve, plug valve, such as louver valves, can be widely used in petroleum, chemical, water, marine, pulp and paper, power, heating, light industry and other industries.

## Technical Specification:

Model: CG-HQ

Working pressure: 11Mpa

Rotation angle: 90±5 degree

Ambient temperature: -20 °C to 80 °C

## Outside Dimension Of CG-HA Hydraulic Actuator:

Model	CG-HA40	CG-HA50	CG-HA60	CG-HA70	CG-HA80	CG-HA100
ISO Flange	F05-F07	F07-F10	F10-F12	F12	F12-F14	F14-F16
A	291	320	385	492	577	724
B	160	185	212	270	284	324
C	116	140	155	165	180	220
D	130	155	182	240	254	294
E	40	45	50	55	65	70
G	17	17/19	22	27	36	46
Φ F	18	18/22	22/28	28/36	36/42	50
Φ 0	50	70	102	/	125	140
Φ 01	70	102	125	125	140	165
P	4-M6	4-M8	4-M10	/	4-M12	4-M16
P1	4-M8	4-M10	4-M12	4-M12	4-M16	4-M20
b	5/6	6/8	8/10	10	10/12	16
Max Torque	240	400	690	1130	2050	3650

