CENTRIFUGAL PUMP

CIHG Marine Vertical Centrifugal Pump

ISO9001 Supplier

Class Certificate

Export Supply

APPLICATION: 1.CIHG pump is suitable for liquids containing no solid particle, corrosive but similar to water in viscosity, it can be applied to ship petroleum, metallurgy electric power, ...



Key Highlights

Category	Centrifugal Pump
Standard	DIN
Material	If the press exceeds 1.6Mpa when ordering, we will accordingly adjust an...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Centrifugal Pump	**Model / SKU**	CIHG-Marine-Vertical-Centrifugal-Pump
Standard	DIN	**Material**	If the press exceeds 1.6Mpa when ordering, we will accordingly adjust and process the flow parts of pump using cast steel).
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- APPLICATION:
- WORKING CONDITION:

APPLICATION:

1.CIHG pump is suitable for liquids containing no solid particle, corrosive but similar to water in viscosity,

it can be applied to ship petroleum, metallurgy electric power, paper making, food, pharmacy and synthetic fiber, service temperature -20+120℃.

CIHRG pump can be applied to ship, metallurgy, chemical industry, textile industry. paper making, and situations such as restaurant, hotel, pressurized boiler circulation system and housing heating. service temperature <200℃.

CYG pump is suitable for transportation of petroleum products as gasoline, kerosene, diesel oil, as well as synthetic fiber, service temperature 20 -+120C.

WORKING CONDITION:

1. The upper limit of pump wording press is not more than 1.6Mpe, i.e. press in pump suction opening plus pump heads 1.6Mpa. If the press exceeds 1.6Mpa when ordering, we will accordingly adjust and process the flow parts of pump using cast steel).

Clean water or other liquids similar to clean water in physical chemistry property is suitable for transportation.9if conveyance medium contains fine particle,it should be put forward in advance so that we will equip the pump with wearable mechanical seal).

Ambient temperaturec 40C, height above ses level 1000meters, relative humidity < ninety five percent.