

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

IEC 60092 STANDARD CABLE (CHINA TYPE)

## CJ86/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CJ86/NC cable is fire resistant marine power & control Cable, the cable color could be red, black, grey and blue. Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2

...



### Key Highlights

|                      |  |
|----------------------|--|
| <b>Category</b>      | IEC 60092 Standard Cable (China Type)  |
| <b>Standard</b>      | DIN  |
| <b>Material</b>      | Tinned Copper/Mica Tape/<br>Tinned Copper Wire Braided/<br>SHF1 Outer Sheath |
| <b>Weight / Size</b> | IEC 61034-1, IEC61034-2<br>Cores & Size Cores:                               |
| <b>Certificate</b>   | ABS, LR, BV, GL, RINA, DNV,<br>NK, KR, CCS                                   |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

|                      |   |                    |  |
|----------------------|---|--------------------|--|
| <b>Category</b>      | IEC 60092 Standard Cable (China Type)       | <b>Model / SKU</b> | CJ86-NC-Fire-Resistant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured    |
| <b>Standard</b>      | DIN   | <b>Material</b>    | Tinned Copper/Mica Tape/ Tinned Copper Wire Braided/ SHF1 Outer Sheath |
| <b>Weight / Size</b> | IEC 61034-1, IEC61034-2 Cores & Size Cores: | <b>Certificate</b> | ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS                                |
| <b>Warranty</b>      | 12 Months unless specified otherwise        | <b>Origin</b>      | China  |



0.038377s

**CONTENTS**

- China CJ86/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Features
- Cable Construction
- Cores & Size
- Delivery

## China CJ86/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CJ86/NC cable is fire resistant marine power & control Cable, the cable color could be red, black, grey and blue.

### Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : XLPE Insulation

Inner Covering: None

Armour : Tinned Copper Wire Braided

Outer Sheath : Halogen-free Cross Linked Thermoplastic Polyolefin(SHF1)

### Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

### Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300



## Features

Halogen-free, Low Smoke, Fire-Retardant.

## Delivery

We can delivery around the world according to Incoterms 2010.

