

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

IEC 60092 STANDARD CABLE (CHINA TYPE)

CJPF/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(No Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CJPF/SC Cable is Flame Retardant Marine Power and Control Cable with on screen, 0.6/1KV. Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 Insulation ;...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/XLPE insulation/SHF1 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CJPF-SC-Flame-Retardant-Marine-Power-Lighting-Cable-0-6-1KV-No-Armoured
Standard	EN	Material	Tinned Copper/XLPE insulation/SHF1 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China



CONTENTS

- China CJPF/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(No Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CJPF/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(No Armoured):



CJPF/SC Cable is Flame Retardant Marine Power and Control Cable with on screen, 0.6/1KV.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Inner Covering: None

Armour : None

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flame Retardant: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300



Feature

Halogen-free, Low Smoke, Flame retardant.

Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.

