

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

IEC 60092 STANDARD CABLE (CHINA TYPE)

CJPJ85/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CJPJ85/NC Cable is tinned copper wire braided and fire resistant marine power cable, the sheath color is black. Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 ...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	DIN
Material	Tinned Copper/Mica Tape/XLPE insulation/SHF2 sheath/Tinned Copper Wire B...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CJPJ85-NC-Fire-Resistant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
Standard	DIN	Material	Tinned Copper/Mica Tape/XLPE insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2 Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China



CONTENTS

- China CJPJ85/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Features
- Cable Construction
- Cores & Size
- Delivery

China CJPJ85/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CJPJ85/NC Cable is tinned copper wire braided and fire resistant marine power cable, the sheath color is black.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : XLPE Insulation

Inner Covering: Halogen-free Cross Linked Thermoset Polyolefin(SHF2)

Armour :tinned copper Wire Braided

Outer Sheath : Halogen-free Cross Linked Thermoset Polyolefin(SHF2)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300



Features

Halogen-free, Low Smoke, Fire-Retardant.

Delivery

We can delivery around the world according to Incoterms 2010.

