IEC 60092 STANDARD CABLE (CHINA TYPE)

# CKJPF/SC Flame Retardant Marine Control Cable 250V

ISO9001 Supplier

Class Certificate

Export Supply

CKJPF/SC Cable is flame retardant Halogen-free low smoke Marine Control Cable 150/250V. Cable Construction   Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2 I...



## Key Highlights

| | |
|---|---|
| **Category** | IEC 60092 Standard Cable (China Type) |
| **Standard** | DIN |
| **Material** | Tinned Copper/XLPE Insulation/ SHF1 outer sheath |
| **Weight / Size** | IEC 61034-1, IEC61034-2 Cores & Size Cores: |
| **Certificate** | ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | IEC 60092 Standard Cable (China Type) | **Model / SKU** | CKJPF-SC-Flame-Retardant-Marine-Control-Cable-250V |
| **Standard** | DIN | **Material** | Tinned Copper/XLPE Insulation/ SHF1 outer sheath |
| **Weight / Size** | IEC 61034-1, IEC61034-2 Cores & Size Cores: | **Certificate** | ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS |
| **Warranty** | 12 Months unless specified otherwise | **Origin** | China |

**CONTENTS**

- China CKJPF/SC Flame Retardant Marine Control Cable 250V:
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

## China CKJPF/SC Flame Retardant Marine Control Cable 250V:




CKJPF/SC Cable is flame retardant Halogen-free low smoke Marine Control Cable 150/250V.

## Cable Construction

Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Inner Covering: None

Armour : None

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

## Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

## Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,27, 30, 33,37.

Size (sqmm): 0.75, 1, 1.5, 2.5.

## Feature

Halogen-free, Low Smoke, Flame retardant

## Application:

The cable is fixed installation, used for control system in ship or offshore bulding.