IEC 60092 STANDARD CABLE (CHINA TYPE)

CKJPF86/SC Flame Retardant Marine Control Cable 250V (Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CKJPF86/SC Cable is tinned copper wire braided and flame retardant marine control cable 150/250V. Technical Specification: Cable Construction   Conductor: Stranded Tinned Ann...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	DIN
Material	Tinned Copper/XLPE insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	**Model / SKU**	CKJPF86-SC-Flame-Retardant-Marine-Control-Cable-250V-Armoured
Standard	DIN	**Material**	Tinned Copper/XLPE insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF1 Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	**Certificate**	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China CKJPF86/SC Flame Retardant Marine Control Cable 250V (Armoured):
- Cable Construction
- Cores & Size
- Application:
- Technical Specification:
- Standards
- Feature

China CKJPF86/SC Flame Retardant Marine Control Cable 250V (Armoured):



CKJPF86/SC Cable is tinned copper wire braided and flame retardant marine control cable 150/250V.

Technical Specification:

Cable Construction

Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Tinned Copper Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,27, 30, 33,37.

Size (sqmm): 0.75, 1, 1.5, 2.5.

Feature

Halogen-free, Low Smoke, Flame retardant

Application:

The cable is fixed installation, used for control system in ship or offshore bulding.