IEC 60092 STANDARD CABLE (CHINA TYPE)

CKJPF96/SC Flame Retardant Marine Control Cable 250V (Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CKJPF96/SC Cable is galvanized steel wire braided and flame retardant marine control cable 150/250V. Cable Construction   Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class ...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	DIN
Material	Tinned Copper/XLPE insulation/SHF1 sheath/Galvanized Steel Wire Braided/...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	**Model / SKU**	CKJPF96-SC-Flame-Retardant-Marine-Control-Cable-250V-Armoured
Standard	DIN	**Material**	Tinned Copper/XLPE insulation/SHF1 sheath/Galvanized Steel Wire Braided/SHF1 Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	**Surface**	galvanized
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China CKJPF96/SC Flame Retardant Marine Control Cable 250V (Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CKJPF96/SC Flame Retardant Marine Control Cable 250V (Armoured):



CKJPF96/SC Cable is galvanized steel wire braided and flame retardant marine control cable 150/250V.

Cable Construction

Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Galvanized Steel Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,27, 30, 33,37.

Size (sqmm): 0.75, 1, 1.5, 2.5.

Feature

Halogen-free, Low Smoke, Flame retardant

Application:

The cable is fixed installation, used for control system in ship or offshore bulding.