


MAGNETIC COUPLING AND SPEED REGULATING DEVICE

COB Standard Type Permanent Magnet Eddy Current Transmission

- ISO9001 Supplier
- Class Certificate
- Export Supply

Standard Type Permanent Magnet Eddy Current Transmission mainly include the copper rotor, Permanent magnet rotor. Generally copper rotor (Steel rotor with copper ring) connect with motor shaft, Permanent magnet rotor (...)

	<h3 style="margin: 0;">Key Highlights</h3> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Category</td> <td style="padding: 5px;">Magnetic Coupling and Speed Regulating Device</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Standard</td> <td style="padding: 5px;">DIN</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Material</td> <td style="padding: 5px;">Generally copper rotor (Steel rotor with copper ring) connect with motor...</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Weight / Size</td> <td style="padding: 5px;">Simple structure, small size, easy to install, adapt to work in harsh co...</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Certificate</td> <td style="padding: 5px;">ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS</td> </tr> </table> <p style="font-size: small; padding: 5px;">We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	Category	Magnetic Coupling and Speed Regulating Device	Standard	DIN	Material	Generally copper rotor (Steel rotor with copper ring) connect with motor...	Weight / Size	Simple structure, small size, easy to install, adapt to work in harsh co...	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Category	Magnetic Coupling and Speed Regulating Device										
Standard	DIN										
Material	Generally copper rotor (Steel rotor with copper ring) connect with motor...										
Weight / Size	Simple structure, small size, easy to install, adapt to work in harsh co...										
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS										

Technical Specifications			
Category	Magnetic Coupling and Speed Regulating Device	Model / SKU	COB-Standard-Type-Permanent-Magnet-Eddy-Current-Transmission
Standard	DIN	Material	Generally copper rotor (Steel rotor with copper ring) connect with motor shaft, Permanent magnet rotor (aluminum rotor with permanent magnets) connect with load shaft.
Weight / Size	Simple structure, small size, easy to install, adapt to work in harsh conditions.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China COB Standard Type Permanent Magnet Eddy Current Transmission:

Standard Type Permanent Magnet Eddy Current Transmission mainly include the copper rotor, Permanent magnet rotor. Generally copper rotor (Steel rotor with copper ring) connect with motor shaft, Permanent magnet rotor (aluminum rotor with permanent magnets) connect with load shaft. There is only An air-gap between copper rotor and permanent magnet rotor without mechanical connection for Trans missing the torque. When the motor rotates, the copper ring of copper rotor cut the magnetic field Lines of permanent magnet, generate inductive eddy current and creates a magnetic field in copper rotor, Thereby transmitting torque across the air-gap. Allowed adjust the air-gap within a certain range to Achieve the required torque transmission and speed delivery requirements.

Few day-maintenance, low operation cost, almost maintenance-free products

Accept misalignment, centration error 5mm (max), angular error 2.5 (max) .

With overload protection, increase overall system reliability, eliminate the amazement of system for Overload

Improve the motor starting capability and come true the motor soft start / stop. And, reduce shock and Vibration, coordinate between multi-machine-driven load distributions.

Extend the life of the transmission system components.

Simple structure, small size, easy to install, adapt to work in harsh conditions.

Allowed adjusted the air-gap to achieve the required torque transmission and speed delivery Requirements.

Supply a variety of special shaft or installation size.

