CENTRIFUGAL PUMP

CQX (W) Series Submersible Sewage Pump

ISO9001 Supplier

Class Certificate

Export Supply

1. High Quality 2. Large displacement and high effciency3. Easy and stable operation4. Competitive price5. Fast Delivery



Key Highlights

Category	Centrifugal Pump
Standard	DIN
Material	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Centrifugal Pump	**Model / SKU**	CQX-W-Series-Submersible-Sewage-Pump
Standard	DIN	**Material**	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
Certificate	CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- CQX(W) series deep-well limber pump
- Performance parameter
- General discription

CQX(W) series deep-well limber pump

1. High Quality
2. Large displacement and high effciency
3. Easy and stable operation
4. Competitive price
5. Fast Delivery

General discription

The pump is basically applicable to marine emergency survival system and removal of accumulated water in the cabin. It is widely used to let sludge, liquid waste, city life sludge, which with some solid and fiber in town planning, pumping station, and architecture and so on. Similarly, it is used to fire damper, irrigation in country.

The motor’s insulated grade is F, crust grade Is IPx8.

Power between 1.5-7.5kw, a leak measure electrode had been setting in the motor body, when the leak measure electrode incepted a signal; the controller emitted warm and protected the pump. Power above 7.5kw, a bobber switch had been setting in the motor body; a leak measure electrode had been setting in the junction box and oil room; superheat and over loading protect equipment had been setting in the motor bearing.

Performance parameter

Tpye	Capacity	Head	efficiency	power	rpm	Throughout max.
Q (m3/h)	H (m)	%	P (kw)	N (r/min)	mm	
CQX(W)10-10-1	10	10	44	1	2900	25
CQX(W)15-7-1	15	7	47	1		25
CQX(W)10-15-15	10	15	44	1.5		25
CQX(W)15-10-10	15	10	47	1.5		25
CQX(W)25-8-1.5	25	8	51	1.5		25
CQX(W)15-20-2.2	15	20	47	2.2		40
CQX(W)25-14-2.2	25	14	50	2.2		40
CQX(W)40-10-2.2	40	10	54	2.2		40
CQX(W)20-22-3	20	22	49	3		40
CQX(W)30-16-3	30	16	52	3		40
CQX(W)40-12-3	40	12	54	3		40
CQX(W)20-25-4	20	25	49	4		40
CQX(W)30-18-4	30	18	52	4		40
CQX(W)40-15-4	40	15	54	4		40
CQX(W)60-13-4	60	13	57	4		40

CQX(W)25-30-5.5	25	30	52	5.5	1470	25
CQX(W)30-21-5.5	30	21	52	5.5		50
CQX(W)45-18-5.5	45	18	55	5.5		50
CQX(W)65-15-5.5	65	15	45	5.5		50
CQX(W)70-14-5.5	70	14	58	5.5		50
CQX(W)100-8-5.5	100	8	60	5.5		50
CQX(W)20-40-7.5	20	40	51	7.5	2900	40
CQX(W)45-30-7.5	45	30	52	7.5	1470	45
CQX(W)50-27-7.5	50	27	55	7.5		45
CQX(W)70-20-7.5	70	20	58	7.5		45
CQX(W)100-13-7.5	100	13	60	7.5		50
CQX(W)150-8-7.5	150	8	62	7.5		50
CQX(W)45-32-11	45	32	55	11		50
CQX(W)70-22-11	70	22	58	11		50
CQX(W)100-16-11	100	16	59	11		50
CQX(W)150-10-11	150	10	61	11		50
CQX(W)70-32-15	70	32	58	15		50
CQX(W)100-22-15	100	22	59	15		50
CQX(W)250-13-15	250	13	65	15		50
CQX(W)150-17-15	150	17	62	15		50
CQX(W)150-20-45	150	20	65	15	970	50