

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## HAND PUMP

# CS-20Y.H Hand Pump

CS series pump and I,III hand pump are had operated piston pumps and operate through two action of single jar. It can be used to deliver lube oil,fuel oil,other lubricant oil,fresh water and sea water that do not exceed 60...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Hand Pump
Standard	EN
Weight / Size	Main Technical Data Model Flow rate Q ( m³/h ) Reciprocating Rate (order/mi...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS


We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Hand Pump	Model / SKU	CS-Series-Hand-Pump
Standard	EN	Weight / Size	Main Technical Data Model Flow rate Q ( m³/h ) Reciprocating Rate (order/min) Hand effort (N) Weight (kg) CS-15Y.H 0.6 50 100 3.5 CS-20Y.H 1.2 50 180 5 CS-25Y.H 1.92 50 230 7.5 CS-32Y.H 2.88 50 280 9.5 CS-40Y.H 3.9 50 380 11 I 1.2 80 - 15.5 III 3.9 50 - 38.2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

### China CS-20Y.H Hand Pump:

CS series pump and I,III hand pump are had operated piston pumps and operate through two action of single jar. It can be used to deliver lube oil,fuel oil,other lubricant oil,fresh water and sea water that do not exceed 60°C in temperature and do not have hard particles or fibre. It is used widely of marine, industry, oil depot and transport se



also be regarded as oil-supplying pump for diesel generating unit.

Main Technical Data				
Model	Flow rate Q ( m <sup>3</sup> /h )	Reciprocating Rate (order/min)	Hand effort (N)	Weight (kg)
CS-15Y.H	0.6	50	100	3.5
CS-20Y.H	1.2	50	180	5
CS-25Y.H	1.92	50	230	7.5
CS-32Y.H	2.88	50	280	9.5
CS-40Y.H	3.9	50	380	11
I	1.2	80	-	15.5
III	3.9	50	-	38.2

