

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MEDIUM PRESSURE WATER COOLED MARINE AIR COMPRESSOR

CV-50/30, CV-40/30, Middle Pressure Water Cooling Marine Air Compresso

ISO9001 Supplier

Class Certificate

Export Supply

Description: Model: CV-50/30, CV-40/30, CV-30/30 automatic control unit for marine medium pressure air compressor Type: type V, two row, water cooled, medium pressure piston type, elastic coupling d...



Key Highlights

Category	Medium Pressure Water Cooled Marine Air Compressor
Standard	DIN
Weight / Size	compact structure, high efficiency, light weight, small volume, low noise...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Medium Pressure Water Cooled Marine Air Compressor	Model / SKU	CV-50-30-CV-40-30-Middle-Pressure-Water-Cooling-Marine-Air-Compresso
Standard	DIN	Weight / Size	compact structure, high efficiency, light weight, small volume, low noise, low exhaust temperature, smooth operation;
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Description:
- Product features:
- Warm tips: according to user needs, you can provide:
- Features:
- Product features:
- Technical data:

Product features:

there are single row, V type two stage compression piston type.

It has high efficiency, light weight, small volume, low noise and smooth operation.

Discharge capacity: 20~120 m³/h; rated pressure: 3 MPa.

The products have manual / automatic shutdown, starting, unloading and discharging functions.

It has direct drive and belt drive.

It is suitable for starting the main engine of ships.

Warm tips: according to user needs, you can provide:

1. The two machines are controlled by each other.
2. Temperature control function
3. Inlet pressure controller
4. Exhaust outlet high pressure hose

Technical data:

Model	Displacement		Specified Pressure	Rotating Speed	Motor Power		Dimension (L×W×H)	Weight
	m ³ /h	m ³ /min			Mpa	kW		
CZ-20/30SZK (Direct Connection)	20	0.34	3	960	5.5	7.5	900×600×850	250
CZ-20/30SZK				1000			1070×490×810	225
CV-30/30 (Direct Connection)	30	0.5		720	7.5	10	1230×730×690	330
CV-40/30 (Direct Connection)	40	0.67		870	11	15	1230×730×690	340
CV-50/30 (Direct Connection)	50	0.83		970	11	15	1230×730×690	340
CV-90/30 (Direct Connection)	90	1.5		730	22	30	1600×1010×1050	900
CV-120/30 (Direct Connection)	120	2		975	30	40	1600×1010×1050	1000