

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## CENTRIFUGAL PUMP

# CWL Marine centrifugal pump

CWL Series Self-priming marine pump General description: CWL Series pump is a horizontal single-suction centrifugal pump, seal form for mechanical seal, also can use packing seal. Applicable to ships motor dr...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

Category	Centrifugal Pump
Standard	DIN
Material	Cast Iron, Bronze
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Centrifugal Pump	Model / SKU	CWL-Marine-centrifugal-pump
Standard	DIN	Material	Cast Iron, Bronze
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

<b>CONTENTS</b>	■ CWL Series Self-priming marine pump	■ General description:
	■ Meaning of CWL Model number 32CWL-4	■ Technical Parameter :

## CWL Series Self-priming marine pump

### General description:

CWL Series pump is a horizontal single-suction centrifugal pump, seal form for mechanical seal, also can use packing seal. Applicable to ships motor driven water and cooling water pump, drainage pumps, sanitary drains and household water pumps, transmission medium temperature should be lower than 75°C. This Series of pumps can be factory mine



city water supply and rural irrigation and other uses. According to user applications, in the performance of the same circumstances, the use of different materials, by the user in the order presented.

## Meaning of CWL Model number 32CWL-4

32:The diameter of inlet of pump(mm)

CWL:Marine horizontal centrifugal pump

4: Integral of the pump specific speed divided by 10

## Technical Parameter :

380V/50hz			440V/60hz			
Model	Capacity	Head	Power	Capacity	Head	Power
m3/h	m	kw	m3/h	m	kw	
32CWL-4	4	21	1.1	5	30	2.2
32CWL-3	4	30	1.5	5	43	2.2
40CWL-5	8	21	1.1	10	30	2.2
40CWL-4	8	30	2.2	10	43	3
40CWL-3	8	42	3	10	60	4
50CWL-6	12	21	1.5	14	30	3
50CWL-4.5	12	30	3	14	43	4
50CWL-4	12	42	4	14	60	5.5
50CWL-8	21	21	2.2	25	30	4
50CWL-7	21	30	4	25	43	5.5
50CWL-5	21	42	5.5	25	60	7.5
50CWL-3.5	21	60	7.5	25	86	15
65CWL-11	35	21	4	43	30	7.5
65CWL-8	35	30	5.5	43	43	11
65CWL-6	35	42	7.5	43	60	15
80CWL-14	60	21	5.5	72	30	11
80CWL-11	60	30	7.5	72	43	15
80CWL-8	60	42	11	72	60	22
80CWL-6	60	60	18.5	72	86	30
80CWL-5.5	60	75	22	72	108	37
100CWL-18	100	21	11	120	30	15
100CWL-14	100	30	15	120	43	22
100CWL-11	100	42	18.5	120	60	



100CWL-8	100	60	30	120	86	55
100CWL-6	100	85	37	120	122	75
150CWL-18	160	13	11	192	18.5	15
200CWL-12	300	30	37	360	43	75
200CWL-18	400	21	30	480	30	55