

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

SEWAGE TREATMENT PLANT

CWSC Series Sewage Treatment Plant

Suitable for 10-100 persons

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Sewage Treatment Plant
Standard	EN
Material	Carbon Steel
Weight / Size	The effusion of this plant can meet the amended convention of MAPOL 73/7...
Certificate	CCS certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Sewage Treatment Plant	Model / SKU	CWSC-Series-Sewage-Treatment-Plant
Standard	EN	Material	Carbon Steel
Weight / Size	The effusion of this plant can meet the amended convention of MAPOL 73/78 issued by international maritime organization, and fully compliance the resolution MEPC.227(64) "revised guidelines on implementation of effluent standards and performance tests for sewage treatment plants" Model Parameter CSWC CSWC CSWC CSWC CSWC CSWC CSWC CSWC -10 -20 -30 -40 -60 -80 -100 -120 -150 -200 Capacity(m3/d) 1.50 3.00 4.50 6.00 9.00 12.00 15.00 18.00 22.50 30.00 Electrical System 380V/50Hz 440V/60Hz Power (kw) 3.20 3.20 3.50 3.50 4.00 4.00 5.00 5.00 5.50 5.50 Net weight(kg) 650 750 830 1050 1380 1600 1850 2200 2500 2800 Outline demension L(mm) 1440 1440 1560 1760 2160 2820 3220 3620 4520 5820 W(mm) 1270 1470 1670 1870 1970 2170 2270 2270 2270 H(mm) 1580 1780 1880 1880 1980 1980 2080 2080 2080 2080	Certificate	CCS certificate
Warranty	12 Months unless specified otherwise	Origin	China

Product Description:

Small oil-water separatorsuitable for small vessels, the price is very cheap.

Due to adopt the sequence batch reactor (SBR) and UV disinfection technique,the equipment features with advanced technology,reasonable process,stock load capability,compact structure,no secondary pollution etc.

The effusion of this plant can meet the amended convention of MAPOL 73/78 issued by international maritime organization, and fully compliance the resolution MEPC.227(64) "revised guidelines on implementation of effluent standards and performance tests for sewage treatment plants"

Model	CSWC	CSWC	CSWC	CSWC	CSWC	CSWC	CSWC	CSWC	CSWC	CSWC	
	-10	-20	-30	-40	-60	-80	-100	-120	-150	-200	
Capacity(m3/d)	1.50	3.00	4.50	6.00	9.00	12.00	15.00	18.00	22.50	30.00	
Electrical System	380V/50Hz 440V/60Hz										
Power (kw)	3.20	3.20	3.50	3.50	4.00	4.00	5.00	5.00	5.50	5.50	
Net weight(kg)	650	750	830	1050	1380	1600	1850	2200	2500	2800	
Outline demension	L(mm)	1440	1440	1560	1760	2160	2820	3220	3620	4520	5820
	W(mm)	1270	1470	1670	1870	1970	2170	2270	2270	2270	2270
	H(mm)	1580	1780	1880	1880	1980	1980	2080	2080	2080	2080