

VORTEX PUMP

CX Series Marine Single vortex pump

CX Series Marine Single vortex pump General description CX Series Marine Single vortex pump primarily as a supporting marine auxiliary boiler system used to pump water transportation can also be put to othe...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Vortex Pump
Standard	EN
Material	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Vortex Pump	Model / SKU	CX-Series-Marine-Single-vortex-pump
Standard	EN	Material	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ CX Series Marine Single vortex pump ■ Model description 	<ul style="list-style-type: none"> ■ General description ■ Main Parameter
-----------------	--	---



CX Series Marine Single vortex pump

General description

CX Series Marine Single vortex pump primarily as a supporting marine auxiliary boiler system used to pump water transportation can also be put to other uses.

Model description

20CX8

20: inlet diameter 20mm

cx: Marine vortex pump

8: than number of revolutions

Main Parameter

泵型号 Type	流量 m³/h	扬程 mH ₂ O	转速 (r/min)	配用电机 With motor		泵质量 (Kg)
				功率(KW)	型号(type)	
20CX-6	0.7	75	2825	1.1	Y90L2-2-H(B3)	57
20CX-7	1.0	85	2840	1.5	Y90S-2-H(B3)	62
20CX-8	1.5	85	2840	2.2	Y90L-2-H(B3)	67
20CX-10	2.2	85	2880	3.0	Y100L-2-H(B3)	76
25CX-11	3.0	85	2880	3.0	Y100L-2-H(B3)	77
32CX-13	4.0	85	2990	5.5	Y132-S1-2-H(B3)	96
32CX-14	5.0	85	2900	7.5	Y132-S2-2-H(B3)	115
40CX-12	5.0	105	2830	11	Y1180M1-2-H(B3)	140

外型安装尺寸 Installation and external dimensions																
泵型号Type	L	B1	H	A	B	E	n1-d	h1	h	M	Dg	D2	D1	D	h2	n2-d2
20CX-6	436	165	305	100	125	200	4-φ10	15	80	126	φ20	φ48	φ68	φ85	14	4-φ13
20CX-7	654	200	405	370	165	80	4-φ18	20	180	120	φ20	φ48	φ68	φ95	14	4-φ13
20CX-8	683	200	415	412	165	80	4-φ18	12	175	120	φ20	φ48	φ68	φ95	14	4-φ13
20CX-10	716	230	427	440	195	80	4-φ18	12	202	120	φ20	φ48	φ68	φ95	14	4-φ13
25CX-11	723	230	432	440	195	82.5	4-φ18	12	202	124	φ25	φ56	φ73	φ105	14	4-φ11
32CX-14	853	260	452	450	222	130	4-φ18	12	212	134	φ32	φ64	φ83	φ115	15	6-φ15

