MARINE NAVIGATION SIGNAL LIGHT

CXD8 Daylight Signal Light

ISO9001 Supplier

Class Certificate

Export Supply

CXD8 Daylight Signal Light Voltage: 24V Power:60W Light Pillar Angle:6o Light Intensity:60000cd Telescope Magnification:4 Telescope Visual Angle:3o Visibility:2n.m Lamp Holder:G6.35 Plug:25M-4A Four Pin Prote...



Key Highlights

Category	Marine Navigation Signal Light
Standard	EN
Weight / Size	Dia9.5 Weight:2.6kgs CXD8-CDX Charger Input:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Navigation Signal Light	**Model / SKU**	CXD8-Daylight-Signal-Light
Standard	EN	**Weight / Size**	Dia9.5 Weight:2.6kgs CXD8-CDX Charger Input:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- CXD8 Daylight Signal Light
- CXD8-CDX Charger

CXD8 Daylight Signal Light

Voltage: 24V
Power:60W
Light Pillar Angle:6o
Light Intensity:60000cd
Telescope Magnification:4
Telescope Visual Angle:3o

Visibility:2n.m
Lamp Holder:G6.35
Plug:25M-4A Four Pin
Protection Class:IP44
Cable Diameter: Dia9.5
Weight:2.6kgs



CXD8-CDX Charger

Input: AC110V/60Hz, AC-220V/50Hz/60Hz
Output: AC24V,AC12V/DC24V.DC12V
Capacity:7Ah
Temperature:-25-45 Ceisus Dgree
Socket: 25-4B, 25-3B
Protection Class:IP56
Weight:3.6KGS




jinbomarine.com