VORTEX PUMP

CXZ Series Marine Self-Priming Vortex Fresh Water Pump

ISO9001 Supplier

Class Certificate

Export Supply

CXZ Series Marine Self-Priming Vortex Fresh Water Pump CXZ Series Marine Self-Priming Vortex Pump is used to pumping fresh and seawater for drinking, washing and sanitary in the vessel. Main Spe...



Key Highlights

Category	Vortex Pump
Standard	EN
Material	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
Weight / Size	Main Specification Type Capacity Head (NPSH)r Speed Shaft power Motor po...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Vortex Pump	**Model / SKU**	CXZ-Series-Marine-Self-Priming-Vortex-Fresh-Water-Pump
Standard	EN	**Material**	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
Weight / Size	Main Specification Type Capacity Head (NPSH)r Speed Shaft power Motor power Suction head Efficiency Unit weight (m3/h) (l/s) (m) (m) (r/min) (kw) (kw) (m) (%) (kg) 20CXZ-35 1 0.3 35 7 2900 0.43 0.75 3 20 42 32CXZ-25 3.5 1 28 7 2900 1.48 1.5 3 18 57 32CXZ-40 3 0.8 40 6 2900 1.82 2.2 4 18 57 40CXZ-30 9 2.5 30 6 2900 2.54 4 4 29 80	**Certificate**	CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- CXZ Series Marine Self-Priming Vortex Fresh Water Pump
- Main Specification



CXZ Series Marine Self-Priming Vortex Fresh Water Pump

CXZ Series Marine Self-Priming Vortex Pump is used to pumping fresh and seawater for drinking, washing and sanitary in the vessel.

Main Specification

Type	Capacity		Head	(NPSH)r	Speed	Shaft power	Motor power	Suction head	Efficiency	Unit weight
	(m3/h)	(l/s)	(m)	(m)	(r/min)	(kw)	(kw)	(m)	(%)	(kg)
20CXZ-35	1	0.3	35	7	2900	0.43	0.75	3	20	42
32CXZ-25	3.5	1	28	7	2900	1.48	1.5	3	18	57
32CXZ-40	3	0.8	40	6	2900	1.82	2.2	4	18	57
40CXZ-30	9	2.5	30	6	2900	2.54	4	4	29	80