

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE OIL WATER SEPERATOR

CY-2A 15ppm Bilge Alarm Mini Type

Main Feature: Products Name CY-2A (mini type) 15ppm Bilge Alarm Measure range 0 - 30ppm Accuracy ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Oil Water Seperator
Standard	EN
Weight / Size	General working situation 2W Print working situation 7W Protection grade...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Oil Water Seperator	Model / SKU	CY-2A-15ppm-Bilge-Alarm-Mini-Type
Standard	EN	Weight / Size	General working situation 2W Print working situation 7W Protection grade IP45 Main Dimension 210mm×152mm×45mm Weight 2.8 Kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

Main Feature:

Products Name	CY-2A (mini type) 15ppm Bilge Alarm
Measure range	0 - 30ppm
Accuracy	Better than ±5ppm (when 15ppm)
Display of measurement value	LCD screen display

Alarm indication	2 ways red LED
Working point of alarm	15 ppm
Alarm delay 1	0 second
Alarm delay 2	4 seconds
Alarm output	2 channels of relay output
Rated value of alarm relays	3A, 250VAC, non- inductive
Output signal	4 - 20mA
Detection of feedback signal of output of alarm relays	2 channels of operation statue contact detection
Data of alarm data	storage and printing output
Ambient temperature	+1°C - +55°C
Relative humidity	≤93%
Temperature of sample water	+1°C - +40°C
Pressure of sampling water	0.1-0.6 MPa
Flow rate of sampling water	0.1- 4L/min
Power supply	220VAC or DC24V, 50/60Hz
Power consumption:	
General working situation	2W
Print working situation	7W
Protection grade	IP45
Main Dimension	210mm×152mm×45mm
Weight	2.8 Kg