

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE COMMUNICATION EQUIPMENT

## CY-VH02 Marine VHF Interphone

CY-VH02 Marine VHF Interphone with excellent waterproof function,use it 1 meter under water,it can keep watertight in 5 minutes,good corrosion resistance,it can adapt the severe environment on the vessel,easy to operate,...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Marine Communication Equipment
Standard	EN
Weight / Size	< +1.5kHz Size (W x H x D):
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Marine Communication Equipment	Model / SKU	CY-VH02-Marine-VHF-Interphone
Standard	EN	Weight / Size	< +1.5kHz Size (W x H x D):
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

### China CY-VH02 Marine VHF Interphone:

CY-VH02 Marine VHF Interphone with excellent waterproof function,use it 1 meter under water,it can keep watertight in 5 minutes,good corrosion resistance,it can adapt the severe environment on the vessel,easy to operate,unskilled person can use it too,and it can be operate by one hand only.Good property,High reliable.

Frequency Range: 154-163MHz

Channel Spacing: 25kHz (12.5kHz optional)

Working Temperature: -20°C to +55°C

Sensitivity: 0.18μV for 12 dB SINAD

Adjacent Channel Power: > 70 dB

Blocking: > 70 dB

Spurious Response: > 70 dB

Modulation Distortion: < 5%

intermodulation Immunity: > 68 dB

Radio Frequency Output Power : 1W (Lo)/5W (Hi)

Frequency Tolerance : < +1.5kHz

Size (W x H x D): 56 x 133 x 27.5 mm (not include antenna and button )

Weight: 280 g (include battery,button and antenna)