

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

SEWAGE PUMP


## CYW Series Marine Sewage Pump

Main Specification Type Capacity Head Efficiency Power Speed Voltage ...

ISO9001 Supplier

Class Certificate

Export Supply

	Key Highlights	
	Category	Sewage Pump
	Standard	EN
	Material	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft
	Weight / Size	Main Specification Type Capacity Head Efficiency Power Speed Voltage Cur...
Certificate	CCS	
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>		



**Technical Specifications**

<b>Category</b>	Sewage Pump	<b>Model / SKU</b>	CYW-Series-Sewage-Pump
<b>Standard</b>	EN	<b>Material</b>	Cast iron pump cast, Bronze impeller, Stainless steel pump shaft

**Weight / Size**

Main Specification Type Capacity  
 Head Efficiency Power Speed  
 Voltage Current Port Weight  
 (m3/h) (l/s) (m) (%) (kw) (r/min) (V)  
 (A) (mm) (kg) 10-10-1 10 2.8 10  
 44 1 2900 380 3.2 50 29 15-7-1 15  
 4.2 7 47 1 2900 380 3.2 50 29 10-  
 15-1.5 10 2.8 15 44 1.5 2900 380  
 4.3 50 32 15-10-1.5 15 4.2 10 47  
 1.5 2900 380 4.3 50 32 25-8-1.5  
 25 6.9 8 51 1.5 2900 380 4.3 50  
 32 15-20-2.2 15 4.2 20 47 2.2  
 2900 380 4.9 65 45 25-14-2.2 25  
 6.9 14 50 2.2 2900 380 4.9 65 45  
 40-10-2.2 40 11.1 10 54 2.2 2900  
 380 4.9 65 45 20-22-3 20 5.6 22  
 49 3 2900 380 6.4 65 45 30-16-3  
 16 4.4 16 52 3 2900 380 6.4 65 45  
 40-12-3 40 11.1 12 54 3 2900 380  
 6.4 65 45 20-25-4 20 5.6 25 49 4  
 2900 380 8.2 65 75 30-18-4 30 8.3  
 18 52 4 2900 380 8.2 65 75 40-15-  
 4 40 11.1 15 54 4 2900 380 8.2 65  
 75 60-13-4 60 16.7 13 57 4 2900  
 380 8.2 65 75 25-30-5.5 25 6.9 30  
 52 5.5 1470 380 12 50 75 30-21-  
 5.5 30 8.3 21 52 5.5 1470 380 12  
 100 175 45-18-5.5 45 12.5 18 55  
 5.5 1470 380 12 100 175 65-15-  
 5.5 65 18.1 15 45 5.5 1470 380 12  
 100 175 70-14-5.5 70 19.4 14 58  
 5.5 1470 380 12 100 175 100-8-  
 5.5 100 27.8 8 60 5.5 1470 380 12  
 100 175 20-40-7.5 20 5.6 40 51  
 7.5 2900 380 16 80 200 45-30-7.5  
 45 12.5 30 52 7.5 1470 380 16  
 100 200 50-27-7.5 50 13.9 27 55  
 7.5 1470 380 16 100 200 70-20-  
 7.5 70 19.4 20 58 7.5 1470 380 16  
 100 200 100-13-7.5 100 27.8 13  
 60 7.5 1470 380 16 100 200 150-  
 8-7.5 150 41.7 8 62 7.5 1470 380  
 16 150 200 45-32-11 45 12.5 32  
 55 11 1470 380 24.1 100 280 70-  
 22-11 70 19.4 22 58 11 1470 380  
 24.1 100 280 100-16-11 100 27.8  
 16 59 11 1470 380 24.1 150 280  
 150-10-11 150 41.7 10 61 11 1470  
 380 24.1 150 280 70-32-15 70  
 19.4 32 58 15 1470 380 24.1 100  
 280 100-22-15 100 27.8 22 59 15  
 1470 380 24.1 100 280 250-13-15

**Certificate**

**CCS**



	250 69.4 13 65 15 1470 380 24.1 150 280 150-17-15 150 41.7 17 62 15 1470 380 24.1 150 280 500-20- 45 500 138.9 20 65 45 970 380 84 200 1400		
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China



## Main Specification

Type	Capacity		Head (m)	Efficiency (%)	Power (kw)	Speed (r/min)	Voltage (V)	Current (A)	Port (mm)	Weight (kg)
	(l / s)	(m <sup>3</sup> / h)								
10-10-1	10	2.8	10	44	1	2900	380	3.2	50	29
15-7-1	15	4.2	7	47	1	2900	380	3.2	50	29
10-15-1.5	10	2.8	15	44	1.5	2900	380	4.3	50	32
15-10-1.5	15	4.2	10	47	1.5	2900	380	4.3	50	32
25-8-1.5	25	6.9	8	51	1.5	2900	380	4.3	50	32
15-20-2.2	15	4.2	20	47	2.2	2900	380	4.9	65	45

25-14-2.2	2 5	6 . 9	14	50	2.2	2900	380	4.9	65	45
40-10-2.2	4 0	1 1 . 1	10	54	2.2	2900	380	4.9	65	45
20-22-3	2 0	5 . 6	22	49	3	2900	380	6.4	65	45
30-16-3	1 6	4 . 4	16	52	3	2900	380	6.4	65	45
40-12-3	4 0	1 1 . 1	12	54	3	2900	380	6.4	65	45
20-25-4	2 0	5 . 6	25	49	4	2900	380	8.2	65	75
30-18-4	3 0	8 . 3	18	52	4	2900	380	8.2	65	75
40-15-4	4 0	1 1 . 1	15	54	4	2900	380	8.2	65	75
60-13-4	6 0	1 6 . 7	13	57	4	2900	380	8.2	65	75
25-30-5.5	2 5	6 . 9	30	52	5.5	1470	380	12	50	75
30-21-5.5	3 0	8 . 3	21	52	5.5	1470	380	12	100	175
45-18-5.5	4 5	1 2 . 5	18	55	5.5	1470	380	12	100	175
65-15-5.5	6 5	1 8 . 1	15	45	5.5	1470	380	12	100	175
70-14-5.5	7 0	1 9 . 4	14	58	5.5	1470	380	12	100	175

100-8-5.5	1 0 0	2 7 8	8	60	5.5	1470	380	12	100	175
20-40-7.5	2 0	5 6	40	51	7.5	2900	380	16	80	200
45-30-7.5	4 5	1 2 5	30	52	7.5	1470	380	16	100	200
50-27-7.5	5 0	1 3 9	27	55	7.5	1470	380	16	100	200
70-20-7.5	7 0	1 9 4	20	58	7.5	1470	380	16	100	200
100-13-7.5	1 0 0	2 7 8	13	60	7.5	1470	380	16	100	200
150-8-7.5	1 5 0	4 1 7	8	62	7.5	1470	380	16	150	200
45-32-11	4 5	1 2 5	32	55	11	1470	380	24.1	100	280
70-22-11	7 0	1 9 4	22	58	11	1470	380	24.1	100	280
100-16-11	1 0 0	2 7 8	16	59	11	1470	380	24.1	150	280
150-10-11	1 5 0	4 1 7	10	61	11	1470	380	24.1	150	280
70-32-15	7 0	1 9 4	32	58	15	1470	380	24.1	100	280

100-22-15	1 0 0	2 7 8	22	59	15	1470	380	24.1	100	280
250-13-15	2 5 0	6 9 4	13	65	15	1470	380	24.1	150	280
150-17-15	1 5 0	4 1 7	17	62	15	1470	380	24.1	150	280
500-20-45	5 0 0	1 3 8 9	20	65	45	970	380	84	200	1400