

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

CHAIN SWIVEL

Chain Swivels G402

Main Specification Material: 45# Steel Finish: Spaying Painting , Spraying Plastics, Galvanized
Size Table Size (in) Working Load Limit (lbs) ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chain Swivel
Standard	EN
Material	45# Steel
Weight / Size	45# Steel Finish: Spaying Painting , Spraying Plastics, Galvanized Size T...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



0.046583s

Technical Specifications			
Category	Chain Swivel	Model / SKU	Chain-Swivels-G402
Standard	EN	Material	45# Steel
Weight / Size	45# Steel Finish:Spaying Painting , Spraying Plastics, Galvanized Size Table Size (in) Working Load Limit (lbs) Weight Each (lbs) Dimensions A B C D J M R S T 1/4 850 0.21 1.25 0.69 0.75 1.06 0.69 0.31 2.94 1.69 3.44 5/16 1250 0.39 1.63 0.81 1 1.25 0.81 0.38 3.56 2.06 4.19 3/8 2250 0.75 2 0.94 1.25 1.5 1 0.5 4.31 2.5 5.06 1/2 3600 1.43 2.5 1.31 1.5 2 1.31 0.63 5.44 3.19 6.44 5/8 5200 2.5 3 1.56 1.75 2.38 1.5 0.75 6.56 3.88 7.81 3/4 7200 4.13 3.5 1.75 2 2.63 1.88 0.88 7.19 4.31 8.69 7/8 10000 6.25 4 2.06 2.25 3.06 2.13 1 8.38 5 10.1 1 12500 9 4.5 2.31 2.5 3.5 2.38 1.13 9.63 5.75 11.6 1 1/4 18000 16.37 5.63 2.69 3.13 3.69 3 1.38 11.13 6.75 13.4 1 1/2 45200 49.06 7 4.19 4 4.19 4 2.25 17.13 10 20.1	Surface	Galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<input checked="" type="checkbox"/> Main Specification <input type="checkbox"/> Size Table
-----------------	--


Main Specification

Material: 45# Steel

Finish:Spaying Painting , Spraying Plastics, Galvanized

Size Table

Size (in)	Working Load Limit (lbs)	Weight Each (lbs)	Dimensions									
			A	B	C	D	J	M	R	S	T	
1/4	850	0.21	1.25	0.69	0.75	1.06	0.69	0.31	2.94	1.69	3.44	
5/16	1250	0.39	1.63	0.81	1	1.25	0.81	0.38	3.56	2.06	4.19	



3/8	2250	0.75	2	0.94	1.25	1.5	1	0.5	4.31	2.5	5.06
1/2	3600	1.43	2.5	1.31	1.5	2	1.31	0.63	5.44	3.19	6.44
5/8	5200	2.5	3	1.56	1.75	2.38	1.5	0.75	6.56	3.88	7.81
3/4	7200	4.13	3.5	1.75	2	2.63	1.88	0.88	7.19	4.31	8.69
7/8	10000	6.25	4	2.06	2.25	3.06	2.13	1	8.38	5	10.1
1	12500	9	4.5	2.31	2.5	3.5	2.38	1.13	9.63	5.75	11.6
1 1/4	18000	16.37	5.63	2.69	3.13	3.69	3	1.38	11.13	6.75	13.4
1 1/2	45200	49.06	7	4.19	4	4.19	4	2.25	17.13	10	20.1