

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## LIFEBOAT AND RESCUE BOAT ACCESSORIES

# Complete Set CDHD-60/24 Marine Battery Charger

ISO9001 Supplier

Class Certificate

Export Supply

Description: Marine charging power supply is a switching power supply multifunctional charging power supply using high frequency PWM or PFM modulation technology, with IGBT, field effect power tube and pulse...



### Key Highlights

<b>Category</b>	Lifeboat And Rescue Boat Accessories
<b>Standard</b>	DIN
<b>Weight / Size</b>	Eliminating the bulky and noisy power frequency transformer, the weight ...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

<b>Category</b>	Lifeboat And Rescue Boat Accessories	<b>Model / SKU</b>	Complete-Set-CDHD-60-24-Marine-Battery-Charger
<b>Standard</b>	DIN	<b>Weight / Size</b>	Eliminating the bulky and noisy power frequency transformer, the weight of the whole machine is only a quarter of the thyristor charging power supply.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

#### CONTENTS

- China Complete Set CDHD-60/24 Marine Battery Charger:
- Description:
- Technical data:




## China Complete Set CDHD-60/24 Marine Battery Charger:

### Description:

Marine charging power supply is a switching power supply multifunctional charging power supply using high frequency PWM or PFM modulation technology, with IGBT, field effect power tube and pulse width or frequency modulation integrated controller as the main components.

1. Eliminating the bulky and noisy power frequency transformer, the weight of the whole machine is only a quarter of the thyristor charging power supply.
2. The power supply is provided with multiple functional module options. The whole machine adopts intelligent cooling, which can ensure the reliable operation of the power supply even in the high temperature cabin.
3. This charging power supply is a three-stage automatic charging power supply (constant current equalization charging --- constant voltage equalization charging --- floating charging). The entire process of charging the battery is first entered into equalization charging, and the constant current is automatically completed first, and then constant voltage , When the current drops to near zero, the balanced charging is completed, so that it (manual or automatic) will be transferred to "floating charging" to trickle to maintain the battery in a fully charged state.
4. CDHD series marine charging power supply has type approval certificate issued by China Classification Society.

### Technical data:



Specifications ( Output current )	20~60A
-----------------------------------	--------

Input	Rated voltage	Single-phase 220VAC、 Three-phase 380VAC、 Three-phase 440VAC					
	Input range	Rated voltage $\pm$ 15%					
	Input frequency	45~65HZ					
	Efficiency	$\geq$ 87%					
	Maximum current	<table border="1"> <tbody> <tr> <td>Single-phase 220</td> <td>&lt; 8A</td> </tr> <tr> <td>Three-phase 380</td> <td>&lt; 4A</td> </tr> <tr> <td>Three-phase 440</td> <td>&lt; 3A</td> </tr> </tbody> </table>	Single-phase 220	< 8A	Three-phase 380	< 4A	Three-phase 440
Single-phase 220	< 8A						
Three-phase 380	< 4A						
Three-phase 440	< 3A						
Output	Floating voltage	26.4VDC $\pm$ 0.1V(Can be adjusted according to customer requirements and battery specifications )					
	Average voltage	28.2VDC $\pm$ 0.1V(Can be adjusted according to customer requirements and battery specifications )					
	Average floating charge conversion current	Rated output current10% $\pm$ 1A					
	Regulation accuracy	$\pm$ 1%					
	Output ripple and noise	VPP $\leq$ 300mV					
Function	Alarm and protection functions	Input under voltage protection, input over voltage protection, output under voltage warning, output over voltage protection, output short circuit protection					
	Standard functions	Public warning, fault passive dry contact port (contact limit specification: 32V / 1A)					
	Optional functions	Remote power on / off, remote manual charging, remote manual equalization, standard Modbus-RTU485 communication, external battery temperature compensation, automatic battery identification function					
	Indication and adjustment	Input instructions, work instructions, fault instructions, current regulation					
Working environment	Operating temperature	-15 $^{\circ}$ C~+55 $^{\circ}$ C					
	Storage temperature	-25 $^{\circ}$ C~+85 $^{\circ}$ C					
	Relative humidity	0~95% ( Non-condensing )					
	Atmospheric pressure	70kPa~106kPa					
	Cooling method	Air-cooled					
Standard range	Safety	IEC61000-4-2、 IEC61000-4-3、 IEC61000-4-4、 IEC61000-4-5、 IEC61000-4-6、 IEC60092-101、 IEC60068-2-11					
	Conduction, radiation	CISPR16、 EN55022					
	Certification	CCS Type approval					

Others	Size (WxDxH) mm	105x147x180
	Weight	6kg
	Installation method	Wall mount