

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE FENDER

Cylindrical Rubber Fender

Cylindrical rubber fender also named as Y type fender. It is simple to install and operate, versatile and highly cost effective, this type fender is widely used in shipping and docks. Cylindrical rubber fenders' simp...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fender
Standard	EN
Material	rubber
Weight / Size	The wide range of available sizes means Cylindrical rubber fenders can b...
Certificate	BV,CCS,ABS,mill certificate etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Fender	Model / SKU	Cylindrical-Rubber-Fender
Standard	EN	Material	rubber
Weight / Size	The wide range of available sizes means Cylindrical rubber fenders can be closely matched to each application, and suitable for the berthing of both large and small vessels.	Certificate	BV,CCS,ABS,mill certificate etc.
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Cylindrical Rubber Fender:

- Features:

China Cylindrical Rubber Fender:

Cylindrical rubber fender also named as Y type fender.



It is simple to install and operate, versatile and highly cost effective, this type fender is widely used in shipping and docks. Cylindrical rubber fenders' simple hollow cylinder design can be produced in almost any length and diameter combination to meet specific performance and space requirements. The wide range of available sizes means Cylindrical rubber fenders can be closely matched to each application, and suitable for the berthing of both large and small vessels. Its installation is various— horizontally, vertically or diagonally and can also be adapted to suit wharf corners.

Features:

Simple and economical design,

Easy to be installed and maintained.

Choice of mounting systems to suit different structures and applications

Wide range of available size

Product No.	Length (mm)	Out Diameter (mm)	Inner Diameter (mm)	Weight(kg/m)
Y150	550~5500	150	75	18
Y200		200	100	28
Y250		250	125	45
Y300		300	150	64
Y400		400	200	110
Y500		500	250	175
Y600		600	300	250
Y700		700	350	345
Y800		800	400	450
Y900		900	450	570
Y1000		1000	500	710
Y1100		1100	550	870
Y1200		1200	600	1020
Y1400		1400	700	1400
Y1600		1600	800	1800

