

ELECTRICAL CONNECTORS

DCJXH202 Explosion-proof Junction Box

- ISO9001 Supplier
- Class Certificate
- Export Supply

The scope of application Mainly used for electric connection, circuit connected with the breaker for all kinds of ships, offshore oil, chemical industry and other places which may accumulate inflammable and explosi...



DCJXH202-4

JINBO MARINE

Key Highlights

Category	Electrical Connectors
Standard	EN
Weight / Size	Protection class:IP56.Voltage:550V Current:20A.Cable outside diameter is...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Electrical Connectors	Model / SKU	DCJXH202-Explosion-proof-Junction-Box
Standard	EN	Weight / Size	Protection class:IP56.Voltage:550V Current:20A.Cable outside diameter is diameter 13mm Code Type Weight(kg) 510 DCJXH202-1 1.4 510/2 DCJXH202-2 1.4 510/3 DCJXH202-3 1.5 510/4 DCJXH202-4 1.6
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ The scope of application 	<ul style="list-style-type: none"> ■ Products feature and products certification
-----------------	------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------

The scope of application

Mainly used for electric connection, circuit connected with the breaker for all kinds of ships, offshore oil, chemical industry and other places which may accumulate inflammable and explosive gas.

Products feature and products certification

Increased safety type of explosion-proof junction box, Explosion proof marked IICT6, it can work normally under the temperature -20 °C ~ +50 °C. The shell is made of high strength high quality brass pre-cession manufacturing forming. With good electrical properties and good waterproof performance. Protection class:IP56.Voltage:550V
Current:20A.Cable outside diameter is diameter 13mm

Code	Type	Weight(kg)
510	DCJXH202-1	1.4
510/2	DCJXH202-2	1.4
510/3	DCJXH202-3	1.5
510/4	DCJXH202-4	1.6