FILTER

DDL25 Single Drum Strainer

ISO9001 Supplier

Class Certificate

Export Supply

DDL25 Single Drum Strainer 1.The single drum strainer may act as strainer(first filter)before pump or bypass strainer after pump.meanwhile,it's applicable for filtering heavy oil and with self-sustaining function o...



Key Highlights

Category	Filter
Standard	EN
Material	may be achieved in two options,e.g.straightforward connection or attache...
Weight / Size	DDL25 Single Drum Strainer Technical Parameters Model Structure size Fla...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Filter	**Model / SKU**	DDL25-Single-Drum-Strainer
Standard	EN	**Material**	may be achieved in two options,e.g.straightforward connection or attached in a right-angle.shell of the strainer is made of Q235A, with element designed as stainless steel cage,filtering precision in spec anging from 40 mesh/inch are available upon request.
Weight / Size	DDL25 Single Drum Strainer Technical Parameters Model Structure size Flange Anchor Weight(kg) L H1 H2 H3 H4 Φ D D2 F2 N-DO E 25 112 335 280 213 113 140 98 75 62 4-Φ12 132 11.5 40 180 400 348 298 228 206 150 110 88 4-Φ18 200 40 50 180 452 390 340 270 206 165 125 108 4-Φ18 200 45	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- DDL25 Single Drum Strainer
- DDL25 Single Drum Strainer Technical Parameters

DDL25 Single Drum Strainer

1.The single drum strainer may act as strainer(first filter)before pump or bypass strainer after pump.meanwhile,it's applicable for filtering heavy oil and with self-sustaining function of heating.
2. Connection of single drum strainer: may be achieved in two options,e.g.straightforward connection or attached in a right-angle.shell of the strainer is made of Q235A, with element designed as stainless steel cage,filtering precision in spec anging from 40 mesh/inch are available upon request.
3. The product performs quite effectively in filtering while ensuring efficient pass-through of various oils,which is easy to operate and convenient for maintenance.
4. The single drum strainer is widely applied for filtering lubricant,fuel and heavy oils in oil pipelines attached to various models of diesel generators both onboard and on land,it's also applied for filtering process of petroleum,power,chemical and sewage treatment facilities.

DDL25 Single Drum Strainer Technical Parameters

Model	Structure size						Flange				Anchor	Weight(kg)
	L	H1	H2	H3	H4	Φ	D	D2	F2	N-DO	E	
25	112	335	280	213	113	140	98	75	62	4-Φ12	132	11.5

40	180	400	348	298	228	206	150	110	88	4-Φ18	200	40
50	180	452	390	340	270	206	165	125	108	4-Φ18	200	45