MARINE KITCHEN GALLEY

DXD-T4E Go-cart Sterilizer

ISO9001 Supplier

Class Certificate

Export Supply

Main Technical Parameter Model: DXD-T4E Eletric system(V/Hz): 3~380/50 Power(KW): 4.5 Sterilization temp: ≥120℃ Cubage(L)P: 1100 Sterilization class: 2 star level Conveying weight(kg/layer): ≤25 Structure Fe...



Key Highlights

Category	Marine Kitchen Galley
Standard	DIN
Material	SS
Weight / Size	2 star level Conveying weight(kg/layer):
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Kitchen Galley	**Model / SKU**	DXD-T4E-Go-cart-Sterilizer
Standard	DIN	**Material**	SS
Weight / Size	2 star level Conveying weight(kg/layer):	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- Main Technical Parameter
- Structure Feature

Main Technical Parameter

Model: DXD-T4E
Eletric system(V/Hz): 3~380/50
Power(KW): 4.5
Sterilization temp: ≥120℃
Cubage(L)P: 1100

Sterilization class: 2 star level
Conveying weight(kg/layer): ≤25

Structure Feature

Sterilizer adopts electric heating way, adopts circular fan to rise temperature in the cabinet rapidly and evenly. The outer and inside layer of sterilizer is made of stainless steel, polyurethane foam of heat preservation insulation material to be stuffed between the inside and outside layer. The sterilizer is designed with circuit breaker against over loading and short circuit; The sterilizer is designed with brainpower thermostant, which can randomly set sterilization temperature, thime, heat, preservation temperature. After sterilzing, still can keep heat preservation state (temperature to be controlled into cabinet to be sterilized, with big loading, convenient to move.