

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

RECIPROCATING PUMP

DZB Series Marine Electrical plunger pump

ISO9001 Supplier

Class Certificate

Export Supply

DZB Series Marine Electric Plunger pump General description DZB series pumps are horizontal single cylinder electric plunger pump, which can be used to suck out such liquid as oily water, bilge, fresh water, sea...



Key Highlights

Category	Reciprocating Pump
Standard	CB
Material	cast iron pump case
Weight / Size	TYPE Flowrate m3/h Pressure MPa High absorption m Between the number of ...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Reciprocating Pump	Model / SKU	DZB-Series-Marine-Electrical-plunger-pump
Standard	CB	Material	cast iron pump case
Weight / Size	TYPE Flowrale m3/h Pressure MPa High absorption m Between the number of /min Intel Pipe Diameter mm pump weight Kw Diameter LxMxH DZB-100 0.1 0.3 6 55 15 0.12 249x210x313 DZB-250 0.25 0.3 6 56 25 0.18 310x230x340 DZB-500 0.5 0.3 6 50 25 0.25 370x255x370 DZB- 1000 1 0.3 6 50 40 0.37 390x268x390 DZB- 2000 2 0.3 6 70 40 0.75 452x300x442 DZB- 3000 3 0.3 6 70 50 1.1 609x356x515 DZB- 4000 4 0.3 6 60 60 1.5 718x395x535 DZB- 5000 5 0.3 6 70 60 1.5 718x395x535	Certificate	CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> ■ DZB Series Marine Electric Plunger pump ■ Pump Parameter: 		<ul style="list-style-type: none"> ■ General description

DZB Series Marine Electric Plunger pump

General description

DZB series pumps are horizontal single cylinder electric plunger pump, which can be used to suck out such liquid as oily water, bilge, fresh water, sea water, etc without hard particle or fiber impurities and below 85 degree.

DZB series pumps are the products updated by DZ series pumps. The designing and making of this pump is up to standard of CB/T3160-92 marine electric plunger oily water delivery pump. Marine products are entirely recognized by CCS.

DZB series pumps are especially fit for complement use of oily water processing plant, reducing oil water emulsifiability, increasing separation effect. It features in working safely, convenient operation, easy maintenance, delicate manufacturing, good durability and economic results. Have small volume, low noise characteristics.

Pump Parameter:

TYPE	Flowrale m3/h	Pressure MPa	High absorption m	Between the number of /min	Intel Pipe Diameter mm	pump weight Kw	Diameter LxMxH
							0.048660s

DZB-100	0.1	0.3	6	55	15	0.12	249x210x313
DZB-250	0.25	0.3	6	56	25	0.18	310x230x340
DZB-500	0.5	0.3	6	50	25	0.25	370x255x370
DZB-1000	1	0.3	6	50	40	0.37	390x268x390
DZB-2000	2	0.3	6	70	40	0.75	452x300x442
DZB-3000	3	0.3	6	70	50	1.1	609x356x515
DZB-4000	4	0.3	6	60	60	1.5	718x395x535
DZB-5000	5	0.3	6	70	60	1.5	718x395x535